

**Amendments to the Drawings**

**Amended Figures 1 and 2 are enclosed marked "replacement sheets".**

### **REMARKS/ARGUMENTS**

The Office Action has been carefully considered. It is respectfully submitted that the issues raised are traversed, being hereinafter addressed with reference to the relevant headings appearing in the Detailed Action section of the Office Action.

The Applicant has amended claims. The Applicant respectfully submits that the amendments to the claim set are fully supported by the originally filed specification.

#### ***Specification***

The Applicant enclose a substitute specification, marked-up and clean versions. The details of the amendments as they appear on the marked-up copies are listed below:

At Page 1, table has been added to replace the tables at the back of the specification. Specifically, the tables from Pages 5, 6 and 36 to 42 (of specification as filed) have been merged into one table.

In the last column of the table, "US Patent/Patent Application and Filing Date" has been added to show the corresponding US patent Application numbers or US granted patent numbers and their respective filing dates. No new matter has been added.

At Page 13, line 7, "leave" has been replaced by "able"; at page 14, line 13, "pagewide" has been replaced by "pagewidth"; at page 14, line 27, "45" has been replaced by "Forty-five"; at page 14, line 30, "below" has been replaced by "under the heading "Cross References to Related Applications"".

At Page 6 (of the specification as filed), the paragraphs entitled "Tables of Drop-on-Demand Inkjets" have been moved to Page 15.

At Page 16, line 5, the word printer has been replaced by "print technology"

The Applicants submit that these amendments are merely of a typographical and grammatical nature and that no new matter has been added.

#### ***Drawings***

In paragraph 2 of the Office Action the Examiner has objected that the newly added Figure 2, "ARTCAM CENTRAL PROCESSOR (ACP)" should be changed to "ARTCARD PROCESSOR 2". Furthermore, the number "2/2" should be removed from the drawing.

In view of the objection, "ARTCAM CENTRAL PROCESSOR (ACP)" has been changed to "ARTCARD PROCESSOR 2" and the number "2/2" has been deleted from the replacement sheet.

***Claim Rejections 35 USC § 112***

In paragraph 5, the Examiner has rejected claims 9 to 20 as failing to comply with the written description requirement. In particular, the Examiner has indicated that page 43 (referred to by the Applicant in the previous response) does not include corresponding US Patent which are incorporated by reference. The Applicant now believes that the amended substitute specification overcome this objection.

The Applicant respectfully submits that under the heading "Artcam Technologies", a table is provided in the specification which lists Australian Provisional Numbers, filing date, title, and US Patent/Patent Application and Filing Date. As such these US Patent applications in this table should be incorporated by reference and provide support for claims 9 to 20, we respectfully submit that claims 9 to 20 should not be rejected as lacking support from the specification.

However, in order to expedite the allowance of the current application, the Applicant has cancelled claims 9 to 20. We respectfully request that the Examiner withdraw this rejection.


Very respectfully,

Applicants:



---

KIA SILVERBROOK



---

PAUL LAPSTUN

C/o: Silverbrook Research Pty Ltd  
393 Darling Street  
Balmain NSW 2041, Australia

Email: [kia.silverbrook@silverbrookresearch.com](mailto:kia.silverbrook@silverbrookresearch.com)

Telephone: +612 9818 6633

Facsimile: +61 2 9555 7762



## A DIGITAL CAMERA SYSTEM HAVING MOTION DEBLURRING MEANS

### CROSS REFERENCES TO RELATED APPLICATIONS

The following Australian provisional patent applications are hereby incorporated by cross-reference. For the purposes of location and identification, US patent applications identified by their US patent application serial numbers (USSN) are listed alongside the Australian applications from which the US patent applications claim the right of priority.

#### Ink Jet Printing

A large number of new forms of ink jet printers have been developed to facilitate alternative ink jet technologies for the image processing and data distribution system. Various combinations of ink jet devices can be included in printer devices incorporated as part of the present invention. Australian Provisional Patent Applications relating to these ink jets which are specifically incorporated by cross reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

<u>Australian Provisional Number</u>	<u>Filing Date</u>	<u>Title</u>	<u>US Patent/Patent Application and Filing Date</u>
PO8066	15-Jul-97	Image Creation Method and Apparatus (IJ01)	6,227,652 (July 10, 1998)
PO8072	15-Jul-97	Image Creation Method and Apparatus (IJ02)	6,213,588 (July 10, 1998)
PO8040	15-Jul-97	Image Creation Method and Apparatus (IJ03)	6,213,589 (July 10, 1998)
PO8071	15-Jul-97	Image Creation Method and Apparatus (IJ04)	6,231,163 (July 10, 1998)
PO8047	15-Jul-97	Image Creation Method and Apparatus (IJ05)	6,247,795 (July 10, 1998)
PO8035	15-Jul-97	Image Creation Method and Apparatus (IJ06)	6,394,581 (July 10, 1998)
PO8044	15-Jul-97	Image Creation Method and Apparatus (IJ07)	6,244,691 (July 10, 1998)
PO8063	15-Jul-97	Image Creation Method and Apparatus (IJ08)	6,257,704 (July 10, 1998)
PO8057	15-Jul-97	Image Creation Method and Apparatus (IJ09)	6,416,168 (July 10, 1998)
PO8056	15-Jul-97	Image Creation Method and Apparatus (IJ10)	6,220,694 (July 10, 1998)
PO8069	15-Jul-97	Image Creation Method and Apparatus (IJ11)	6,257,705 (July 10, 1998)
PO8049	15-Jul-97	Image Creation Method and Apparatus (IJ12)	6,247,794

ART34US

			(July 10, 1998)
<u>PO8036</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ13)</u>	<u>6,234,610</u> (July 10, 1998)
<u>PO8048</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ14)</u>	<u>6,247,793</u> (July 10, 1998)
<u>PO8070</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ15)</u>	<u>6,264,306</u> (July 10, 1998)
<u>PO8067</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ16)</u>	<u>6,241,342</u> (July 10, 1998)
<u>PO8001</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ17)</u>	<u>6,247,792</u> (July 10, 1998)
<u>PO8038</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ18)</u>	<u>6,264,307</u> (July 10, 1998)
<u>PO8033</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ19)</u>	<u>6,254,220</u> (July 10, 1998)
<u>PO8002</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ20)</u>	<u>6,234,611</u> (July 10, 1998)
<u>PO8068</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ21)</u>	<u>6,302,528</u> (July 10, 1998)
<u>PO8062</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ22)</u>	<u>6,283,582</u> (July 10, 1998)
<u>PO8034</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ23)</u>	<u>6,239,821</u> (July 10, 1998)
<u>PO8039</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ24)</u>	<u>6,338,547</u> (July 10, 1998)
<u>PO8041</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ25)</u>	<u>6,247,796</u> (July 10, 1998)
<u>PO8004</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ26)</u>	<u>6,557,977</u> (July 10, 1998)
<u>PO8037</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ27)</u>	<u>6,390,603</u> (July 10, 1998)
<u>PO8043</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ28)</u>	<u>6,362,843</u> (July 10, 1998)
<u>PO8042</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ29)</u>	<u>6,293,653</u> (July 10, 1998)
<u>PO8064</u>	<u>15-Jul-97</u>	<u>Image Creation Method and Apparatus (IJ30)</u>	<u>6,312,107</u> (July 10, 1998)
<u>PO9389</u>	<u>23-Sep-97</u>	<u>Image Creation Method and Apparatus (IJ31)</u>	<u>6,227,653</u> (July 10, 1998)
<u>PO9391</u>	<u>23-Sep-97</u>	<u>Image Creation Method and Apparatus (IJ32)</u>	<u>6,234,609</u> (July 10, 1998)
<u>PP0888</u>	<u>12-Dec-97</u>	<u>Image Creation Method and Apparatus (IJ33)</u>	<u>6,238,040</u> (July 10, 1998)
<u>PP0891</u>	<u>12-Dec-97</u>	<u>Image Creation Method and Apparatus (IJ34)</u>	<u>6,188,415</u> (July 10, 1998)
<u>PP0890</u>	<u>12-Dec-97</u>	<u>Image Creation Method and Apparatus (IJ35)</u>	<u>6,227,654</u> (July 10, 1998)

<u>PP0873</u>	<u>12-Dec-97</u>	<u>Image Creation Method and Apparatus (IJ36)</u>	<u>6,209,989</u> (July 10, 1998)
<u>PP0993</u>	<u>12-Dec-97</u>	<u>Image Creation Method and Apparatus (IJ37)</u>	<u>6,247,791</u> (July 10, 1998)
<u>PP0890</u>	<u>12-Dec-97</u>	<u>Image Creation Method and Apparatus (IJ38)</u>	<u>6,336,710</u> (July 10, 1998)
<u>PP1398</u>	<u>19-Jan-98</u>	<u>An Image Creation Method and Apparatus (IJ39)</u>	<u>6,217,153</u> (July 10, 1998)
<u>PP2592</u>	<u>25-Mar-98</u>	<u>An Image Creation Method and Apparatus (IJ40)</u>	<u>6,416,167</u> (July 10, 1998)
<u>PP2593</u>	<u>25-Mar-98</u>	<u>Image Creation Method and Apparatus (IJ41)</u>	<u>6,243,113</u> (July 10, 1998)
<u>PP3991</u>	<u>9-Jun-98</u>	<u>Image Creation Method and Apparatus (IJ42)</u>	<u>6,283,581</u> (July 10, 1998)
<u>PP3987</u>	<u>9-Jun-98</u>	<u>Image Creation Method and Apparatus (IJ43)</u>	<u>6,247,790</u> (July 10, 1998)
<u>PP3985</u>	<u>9-Jun-98</u>	<u>Image Creation Method and Apparatus (IJ44)</u>	<u>6,260,953</u> (July 10, 1998)
<u>PP3983</u>	<u>9-Jun-98</u>	<u>Image Creation Method and Apparatus (IJ45)</u>	<u>6,267,469</u> (July 10, 1998)

#### Ink Jet Manufacturing

Further, the present application may utilize advanced semiconductor fabrication techniques in the construction of large arrays of ink jet printers. Suitable manufacturing techniques are described in the following Australian provisional patent specifications incorporated here by cross-reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

<u>Australian Provisional Number</u>	<u>Filing Date</u>	<u>Title</u>	<u>US Patent/Patent Application and Filing Date</u>
<u>PO7935</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM01)</u>	<u>6,224,780</u> (July 10, 1998)
<u>PO7936</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM02)</u>	<u>6,235,212</u> (July 10, 1998)
<u>PO7937</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM03)</u>	<u>6,280,643</u> (July 10, 1998)
<u>PO8061</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM04)</u>	<u>6,284,147</u> (July 10, 1998)
<u>PO8054</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM05)</u>	<u>6,214,244</u> (July 10, 1998)
<u>PO8065</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM06)</u>	<u>6,071,750</u> (July 10, 1998)
<u>PO8055</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM07)</u>	<u>6,267,905</u> (July 10, 1998)

<u>PO8053</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM08)</u>	<u>6,251,298</u> (July 10, 1998)
<u>PO8078</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM09)</u>	<u>6,258,285</u> (July 10, 1998)
<u>PO7933</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM10)</u>	<u>6,225,138</u> (July 10, 1998)
<u>PO7950</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM11)</u>	<u>6,241,904</u> (July 10, 1998)
<u>PO7949</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM12)</u>	<u>6,299,786</u> (July 10, 1998)
<u>PO8060</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM13)</u>	<u>09/113,124</u> (July 10, 1998)
<u>PO8059</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM14)</u>	<u>6,231,773</u> (July 10, 1998)
<u>PO8073</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM15)</u>	<u>6,190,931</u> (July 10, 1998)
<u>PO8076</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM16)</u>	<u>6,248,249</u> (July 10, 1998)
<u>PO8075</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM17)</u>	<u>6,290,862</u> (July 10, 1998)
<u>PO8079</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM18)</u>	<u>6,241,906</u> (July 10, 1998)
<u>PO8050</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM19)</u>	<u>6,565,762</u> (July 10, 1998)
<u>PO8052</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM20)</u>	<u>6,241,905</u> (July 10, 1998)
<u>PO7948</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM21)</u>	<u>6,451,216</u> (July 10, 1998)
<u>PO7951</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM22)</u>	<u>6,231,772</u> (July 10, 1998)
<u>PO8074</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM23)</u>	<u>6,274,056</u> (July 10, 1998)
<u>PO7941</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM24)</u>	<u>6,290,861</u> (July 10, 1998)
<u>PO8077</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM25)</u>	<u>6,248,248</u> (July 10, 1998)
<u>PO8058</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM26)</u>	<u>6,306,671</u> (July 10, 1998)
<u>PO8051</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM27)</u>	<u>6,331,258</u> (July 10, 1998)
<u>PO8045</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM28)</u>	<u>6,110,754</u> (July 10, 1998)
<u>PO7952</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM29)</u>	<u>6,294,101</u> (July 10, 1998)
<u>PO8046</u>	<u>15-Jul-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM30)</u>	<u>6,416,679</u> (July 10, 1998)

<u>PO8503</u>	<u>11-Aug-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM30a)</u>	<u>6,264,849</u> (July 10, 1998)
<u>PO9390</u>	<u>23-Sep-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM31)</u>	<u>6,254,793</u> (July 10, 1998)
<u>PO9392</u>	<u>23-Sep-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM32)</u>	<u>6,235,211</u> (July 10, 1998)
<u>PP0889</u>	<u>12-Dec-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM35)</u>	<u>6,235,211</u> (July 10, 1998)
<u>PP0887</u>	<u>12-Dec-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM36)</u>	<u>6,264,850</u> (July 10, 1998)
<u>PP0882</u>	<u>12-Dec-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM37)</u>	<u>6,258,284</u> (July 10, 1998)
<u>PP0874</u>	<u>12-Dec-97</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM38)</u>	<u>6,258,284</u> (July 10, 1998)
<u>PP1396</u>	<u>19-Jan-98</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM39)</u>	<u>6,228,668</u> (July 10, 1998)
<u>PP2591</u>	<u>25-Mar-98</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM41)</u>	<u>6,180,427</u> (July 10, 1998)
<u>PP3989</u>	<u>9-Jun-98</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM40)</u>	<u>6,171,875</u> (July 10, 1998)
<u>PP3990</u>	<u>9-Jun-98</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM42)</u>	<u>6,267,904</u> (July 10, 1998)
<u>PP3986</u>	<u>9-Jun-98</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM43)</u>	<u>6,245,247</u> (July 10, 1998)
<u>PP3984</u>	<u>9-Jun-98</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM44)</u>	<u>6,245,247</u> (July 10, 1998)
<u>PP3982</u>	<u>9-Jun-98</u>	<u>A Method of Manufacture of an Image Creation Apparatus (IJM45)</u>	<u>6,231,148</u> (July 10, 1998)

#### Fluid Supply

Further, the present application may utilize an ink delivery system to the ink jet head. Delivery systems relating to the supply of ink to a series of ink jet nozzles are described in the following Australian provisional patent specifications, the disclosure of which are hereby incorporated by cross-reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

<u>Australian Provisional Number</u>	<u>Filing Date</u>	<u>Title</u>	<u>US Patent/Patent Application and Filing Date</u>
<u>PO8003</u>	<u>15-Jul-97</u>	<u>Supply Method and Apparatus (F1)</u>	<u>6,350,023</u> (July 10, 1998)
<u>PO8005</u>	<u>15-Jul-97</u>	<u>Supply Method and Apparatus (F2)</u>	<u>6,318,849</u> (July 10, 1998)
<u>PO9404</u>	<u>23-Sep-97</u>	<u>A Device and Method (F3)</u>	<u>09/113,101</u> (July 10, 1998)



# MEMS Technology

Further, the present application may utilize advanced semiconductor microelectromechanical techniques in the construction of large arrays of ink jet printers.

5 Suitable microelectromechanical techniques are described in the following Australian provisional patent specifications incorporated here by cross-reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

<u>Australian Provisional Number</u>	<u>Filing Date</u>	<u>Title</u>	<u>US Patent/Patent Application and Filing Date</u>
<u>PO7943</u>	<u>15-Jul-97</u>	<u>A device (MEMS01)</u>	
<u>PO8006</u>	<u>15-Jul-97</u>	<u>A device (MEMS02)</u>	<u>6,087,638</u> <u>(July 10, 1998)</u>
<u>PO8007</u>	<u>15-Jul-97</u>	<u>A device (MEMS03)</u>	<u>09/113,093</u> <u>(July 10, 1998)</u>
<u>PO8008</u>	<u>15-Jul-97</u>	<u>A device (MEMS04)</u>	<u>6,340,222</u> <u>(July 10, 1998)</u>
<u>PO8010</u>	<u>15-Jul-97</u>	<u>A device (MEMS05)</u>	<u>6,041,600</u> <u>(July 10, 1998)</u>
<u>PO8011</u>	<u>15-Jul-97</u>	<u>A device (MEMS06)</u>	<u>6,299,300</u> <u>(July 10, 1998)</u>
<u>PO7947</u>	<u>15-Jul-97</u>	<u>A device (MEMS07)</u>	<u>6,067,797</u> <u>(July 10, 1998)</u>
<u>PO7945</u>	<u>15-Jul-97</u>	<u>A device (MEMS08)</u>	<u>Not filed</u>
<u>PO7944</u>	<u>15-Jul-97</u>	<u>A device (MEMS09)</u>	<u>6,286,935</u> <u>(July 10, 1998)</u>
<u>PO7946</u>	<u>15-Jul-97</u>	<u>A device (MEMS10)</u>	<u>6,044,646</u> <u>(July 10, 1998)</u>
<u>PO9393</u>	<u>23-Sep-97</u>	<u>A Device and Method (MEMS11)</u>	<u>09/113,065</u> <u>(July 10, 1998)</u>
<u>PP0875</u>	<u>12-Dec-97</u>	<u>A Device (MEMS12)</u>	<u>09/113,078</u> <u>(July 10, 1998)</u>
<u>PP0894</u>	<u>12-Dec-97</u>	<u>A Device and Method (MEMS13)</u>	<u>09/113,075</u> <u>(July 10, 1998)</u>

# IR Technologies

Further, the present application may include the utilization of a disposable camera system such as those described in the following Australian provisional patent specifications incorporated here by cross-reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

5

<u>Australian Provisional Number</u>	<u>Filing Date</u>	<u>Title</u>	<u>US Patent/Patent Application and Filing Date</u>
<u>PP0895</u>	<u>12-Dec-97</u>	<u>An Image Creation Method and Apparatus (IR01)</u>	<u>6,231,148</u> <u>(July 10, 1998)</u>
<u>PP0870</u>	<u>12-Dec-97</u>	<u>A Device and Method (IR02)</u>	<u>09/113,106</u> <u>(July 10, 1998)</u>
<u>PP0869</u>	<u>12-Dec-97</u>	<u>A Device and Method (IR04)</u>	<u>6,293,658</u> <u>(July 10, 1998)</u>
<u>PP0887</u>	<u>12-Dec-97</u>	<u>Image Creation Method and Apparatus (IR05)</u>	<u>6,614,560</u> <u>(July 10, 1998)</u>
<u>PP0885</u>	<u>12-Dec-97</u>	<u>An Image Production System (IR06)</u>	<u>6,238,033</u> <u>(July 10, 1998)</u>
<u>PP0884</u>	<u>12-Dec-97</u>	<u>Image Creation Method and Apparatus (IR10)</u>	<u>6,312,070</u> <u>(July 10, 1998)</u>
<u>PP0886</u>	<u>12-Dec-97</u>	<u>Image Creation Method and Apparatus (IR12)</u>	<u>6,238,111</u> <u>(July 10, 1998)</u>
<u>PP0871</u>	<u>12-Dec-97</u>	<u>A Device and Method (IR13)</u>	<u>09/113,086</u> <u>(July 10, 1998)</u>
<u>PP0876</u>	<u>12-Dec-97</u>	<u>An Image Processing Method and Apparatus (IR14)</u>	<u>09/113,094</u> <u>(July 10, 1998)</u>
<u>PP0877</u>	<u>12-Dec-97</u>	<u>A Device and Method (IR16)</u>	<u>6,378,970</u> <u>(July 10, 1998)</u>
<u>PP0878</u>	<u>12-Dec-97</u>	<u>A Device and Method (IR17)</u>	<u>6,196,739</u> <u>(July 10, 1998)</u>
<u>PP0879</u>	<u>12-Dec-97</u>	<u>A Device and Method (IR18)</u>	<u>09/112,774</u> <u>(July 10, 1998)</u>
<u>PP0883</u>	<u>12-Dec-97</u>	<u>A Device and Method (IR19)</u>	<u>6,270,182</u> <u>(July 10, 1998)</u>
<u>PP0880</u>	<u>12-Dec-97</u>	<u>A Device and Method (IR20)</u>	<u>6,152,619</u> <u>(July 10, 1998)</u>
<u>PP0881</u>	<u>12-Dec-97</u>	<u>A Device and Method (IR21)</u>	<u>09/113,092</u> <u>(July 10, 1998)</u>

DotCard Technologies

Further, the present application may include the utilization of a data distribution system such as that described in the following Australian provisional patent specifications incorporated here by cross-reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

5

<u>Australian Provisional Number</u>	<u>Filing Date</u>	<u>Title</u>	<u>US Patent/Patent Application and Filing Date</u>
<u>PP2370</u>	<u>16-Mar-98</u>	<u>Data Processing Method and Apparatus (Dot01)</u>	<u>09/112,781</u> <u>(July 10, 1998)</u>
<u>PP2371</u>	<u>16-Mar-98</u>	<u>Data Processing Method and Apparatus (Dot02)</u>	<u>09/113,052</u> <u>(July 10, 1998)</u>

Artcam Technologies

Further, the present application may include the utilization of camera and data processing techniques such as an Artcam type device as described in the following Australian provisional patent specifications incorporated here by cross-reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

10

<u>Australian Provisional Number</u>	<u>Filing Date</u>	<u>Title</u>	<u>US Patent/Patent Application and Filing Date</u>
<u>PO7991</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus (ART01)</u>	<u>09/113,060</u> <u>(July 10, 1998)</u>
<u>PO7988</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus (ART02)</u>	<u>6,476,863</u> <u>(July 10, 1998)</u>
<u>PO7993</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus (ART03)</u>	<u>09/113,073</u> <u>(July 10, 1998)</u>
<u>PO9395</u>	<u>23-Sep-97</u>	<u>Data Processing Method and Apparatus (ART04)</u>	<u>6,322,181</u> <u>(July 10, 1998)</u>
<u>PO8017</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus (ART06)</u>	<u>6,597,817</u> <u>(July 10, 1998)</u>
<u>PO8014</u>	<u>15-Jul-97</u>	<u>Media Device (ART07)</u>	<u>6,227,648</u> <u>(July 10, 1998)</u>
<u>PO8025</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus (ART08)</u>	<u>09/112,750</u> <u>(July 10, 1998)</u>
<u>PO8032</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus (ART09)</u>	<u>6,690,419</u> <u>(July 10, 1998)</u>
<u>PO7999</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus (ART10)</u>	<u>09/112,743</u> <u>(July 10, 1998)</u>
<u>PO7998</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus (ART11)</u>	<u>09/112,742</u> <u>(July 10, 1998)</u>
<u>PO8031</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus (ART12)</u>	<u>09/112,741</u> <u>(July 10, 1998)</u>

ART34US

<u>PO8030</u>	<u>15-Jul-97</u>	<u>Media Device (ART13)</u>	<u>6,196,541</u> <u>(July 10, 1998)</u>
<u>PO7997</u>	<u>15-Jul-97</u>	<u>Media Device (ART15)</u>	<u>6,195,150</u> <u>(July 10, 1998)</u>
<u>PO7979</u>	<u>15-Jul-97</u>	<u>Media Device (ART16)</u>	<u>6,362,868</u> <u>(July 10, 1998)</u>
<u>PO8015</u>	<u>15-Jul-97</u>	<u>Media Device (ART17)</u>	<u>09/112,738</u> <u>(July 10, 1998)</u>
<u>PO7978</u>	<u>15-Jul-97</u>	<u>Media Device (ART18)</u>	<u>09/113,067</u> <u>(July 10, 1998)</u>
<u>PO7982</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus</u> <u>(ART19)</u>	<u>6,431,669</u> <u>(July 10, 1998)</u>
<u>PO7989</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus</u> <u>(ART20)</u>	<u>6,362,869</u> <u>(July 10, 1998)</u>
<u>PO8019</u>	<u>15-Jul-97</u>	<u>Media Processing Method and Apparatus</u> <u>(ART21)</u>	<u>6,472,052</u> <u>(July 10, 1998)</u>
<u>PO7980</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus</u> <u>(ART22)</u>	<u>6,356,715</u> <u>(July 10, 1998)</u>
<u>PO8018</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus</u> <u>(ART24)</u>	<u>09/112,777</u> <u>(July 10, 1998)</u>
<u>PO7938</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus</u> <u>(ART25)</u>	<u>6,636,216</u> <u>(July 10, 1998)</u>
<u>PO8016</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus</u> <u>(ART26)</u>	<u>6,366,693</u> <u>(July 10, 1998)</u>
<u>PO8024</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus</u> <u>(ART27)</u>	<u>6,329,990</u> <u>(July 10, 1998)</u>
<u>PO7940</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus</u> <u>(ART28)</u>	<u>09/113,072</u> <u>(July 10, 1998)</u>
<u>PO7939</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus</u> <u>(ART29)</u>	<u>6,459,495</u> <u>(July 10, 1998)</u>
<u>PO8501</u>	<u>11-Aug-97</u>	<u>Image Processing Method and Apparatus</u> <u>(ART30)</u>	<u>6,137,500</u> <u>(July 10, 1998)</u>
<u>PO8500</u>	<u>11-Aug-97</u>	<u>Image Processing Method and Apparatus</u> <u>(ART31)</u>	<u>6,690,416</u> <u>(July 10, 1998)</u>
<u>PO7987</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus</u> <u>(ART32)</u>	<u>09/113,071</u> <u>(July 10, 1998)</u>
<u>PO8022</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus</u> <u>(ART33)</u>	<u>6,398,328</u> <u>(July 10, 1998)</u>
<u>PO8497</u>	<u>11-Aug-97</u>	<u>Image Processing Method and Apparatus</u> <u>(ART34)</u>	<u>09/113,090</u> <u>(July 10, 1998)</u>
<u>PO8020</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus</u> <u>(ART38)</u>	<u>6,431,704</u> <u>(July 10, 1998)</u>
<u>PO8023</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus</u> <u>(ART39)</u>	<u>09/113,222</u> <u>(July 10, 1998)</u>
<u>PO8504</u>	<u>11-Aug-97</u>	<u>Image Processing Method and Apparatus</u> <u>(ART42)</u>	<u>09/112,786</u>

ART34US

			(July 10, 1998)
<u>PO8000</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus (ART43)</u>	<u>6,415,054</u> (July 10, 1998)
<u>PO7977</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus (ART44)</u>	<u>09/112,782</u> (July 10, 1998)
<u>PO7934</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus (ART45)</u>	<u>6,665,454</u> (July 10, 1998)
<u>PO7990</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus (ART46)</u>	<u>09/113,059</u> (July 10, 1998)
<u>PO8499</u>	<u>11-Aug-97</u>	<u>Image Processing Method and Apparatus (ART47)</u>	<u>6,486,886</u> (July 10, 1998)
<u>PO8502</u>	<u>11-Aug-97</u>	<u>Image Processing Method and Apparatus (ART48)</u>	<u>6,381,361</u> (July 10, 1998)
<u>PO7981</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus (ART50)</u>	<u>6,317,192</u> (July 10, 1998)
<u>PO7986</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus (ART51)</u>	<u>09/113,057</u> (July 10, 1998)
<u>PO7983</u>	<u>15-Jul-97</u>	<u>Data Processing Method and Apparatus (ART52)</u>	<u>09/113,054</u> (July 10, 1998)
<u>PO8026</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus (ART53)</u>	<u>6,646,757</u> (July 10, 1998)
<u>PO8027</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus (ART54)</u>	<u>09/112,759</u> (July 10, 1998)
<u>PO8028</u>	<u>15-Jul-97</u>	<u>Image Processing Method and Apparatus (ART56)</u>	<u>6,624,848</u> (July 10, 1998)
<u>PO9394</u>	<u>23-Sep-97</u>	<u>Image Processing Method and Apparatus (ART57)</u>	<u>6,357,135</u> (July 10, 1998)
<u>PO9396</u>	<u>23-Sep-97</u>	<u>Data Processing Method and Apparatus (ART58)</u>	<u>09/113,107</u> (July 10, 1998)
<u>PO9397</u>	<u>23-Sep-97</u>	<u>Data Processing Method and Apparatus (ART59)</u>	<u>6,271,931</u> (July 10, 1998)
<u>PO9398</u>	<u>23-Sep-97</u>	<u>Data Processing Method and Apparatus (ART60)</u>	<u>6,353,772</u> (July 10, 1998)
<u>PO9399</u>	<u>23-Sep-97</u>	<u>Data Processing Method and Apparatus (ART61)</u>	<u>6,106,147</u> (July 10, 1998)
<u>PO9400</u>	<u>23-Sep-97</u>	<u>Data Processing Method and Apparatus (ART62)</u>	<u>6,665,008</u> (July 10, 1998)
<u>PO9401</u>	<u>23-Sep-97</u>	<u>Data Processing Method and Apparatus (ART63)</u>	<u>6,304,291</u> (July 10, 1998)
<u>PO9402</u>	<u>23-Sep-97</u>	<u>Data Processing Method and Apparatus (ART64)</u>	<u>09/112,788</u> (July 10, 1998)
<u>PO9403</u>	<u>23-Sep-97</u>	<u>Data Processing Method and Apparatus (ART65)</u>	<u>6,305,770</u> (July 10, 1998)
<u>PO9405</u>	<u>23-Sep-97</u>	<u>Data Processing Method and Apparatus (ART66)</u>	<u>6,289,262</u> (July 10, 1998)
<u>PP0959</u>	<u>16-Dec-97</u>	<u>A Data Processing Method and Apparatus (ART68)</u>	<u>6,315,200</u>

ART34US

			(July 10, 1998)
PP1397	19-Jan-98	A Media Device (ART69)	6,217,165 (July 10, 1998)

### Field of the Invention

The present invention relates to digital image processing and in particular discloses A Camera System Having Motion Deblurring Means.

5 Further the present invention relates to the field of digital image cameras and in particular discloses a camera system having motion blur compensating means.

### Background of the Invention

10 Motion blur in the taking of images is a common significant problem. The motion blur normally occurs as a result of movement of the camera while taking the picture or otherwise as a result of movement of objects within an image.

As a result of motion blur, it is often the case that the image taken is non optimal.

### Summary of the Invention

It is an object of the present invention to provide a camera system having the ability to overcome the effects of motion blur.

15 In accordance with the first aspect of the present invention there is provided a camera system for outputting deblurred images, said system comprising;

an image sensor for sensing an image; a velocity detection means for determining any motion of said image relative to an external environment and to produce a velocity output indicative thereof; a processor means interconnected to said image sensor and said velocity detection means and adapted to process said sensed image utilising the velocity output so as to deblurr said image and to output said deblurred image.

20 Preferably, the camera system is connected to a printer means for immediate output of said deblurred image and is a portable handheld unit. The velocity detection means can comprise an accelerometer such as a micro-electro mechanical (MEMS) device.

25

### Brief Description of the Drawings

Notwithstanding any other forms which may fall within the scope of the present invention, preferred forms of the invention will now be described, by way of example only, with reference to the accompanying drawing in which:

30 Fig. 1 illustrates a schematic implementation of the preferred embodiment; and

Fig. 2 is a schematic block diagram of the main Artcam electronic components (as reproduced from Fig. 2 of Australian Provisional Patent Application No. PO7991).

ART34US

As described in Australian Provisional Patent Application No. PO7991, the camera system incorporates an Artcard linear sensor 34 which converts the Artcard data image to electrical signals, which are communicated to the ACP. The linear image sensor is illustrated in Fig. 2, which is a reproduction of Fig. 2 of Australian Provisional Patent Application No. PO7991. The linear image sensor can be fabricated using either CCD or APS CMOS technology. The active length of the linear image sensor is 50 mm, equal to the width of the data array on the Artcard. To satisfy Nyquist's sampling theorem, the resolution of the linear image sensor must be at least twice the highest spatial frequency of the Artcard optical image reaching the linear image sensor. In practice, data detection is easier if the linear image sensor resolution is substantially above this. A resolution of 4800 dpi (189 dpm) is chosen, giving a total of 9,450 pixels. This resolution requires a pixel sensor pitch of 5.3  $\mu\text{m}$ . This can readily be achieved by using four staggered rows of 20  $\mu\text{m}$  pixel sensors.

The linear image sensor is mounted in a special package which includes an LED to illuminate the Artcard via a light-pipe.

The Artcard reader light-pipe can be a molded light-pipe which has several functions:

1. It diffuses the light from the LED over the width of the card using total internal reflection facets.

2. It focuses the light onto a 16  $\mu\text{m}$  wide strip of the Artcard using an integrated cylindrical lens.

3. It focuses light reflected from the Artcard onto the linear image sensor pixels using a molded array of microlenses.

#### Description of Preferred Embodiments

The preferred embodiment is preferably implemented through suitable programming of a hand held camera device such as that described in Australian Provisional Patent Application No. PO7991 filed 15 July, 1997 entitled "Image Processing Method and Apparatus (ART01)", in addition to Australian Provisional Patent Application entitled "Image Processing Method and Apparatus (ART01a)" filed concurrently herewith by the present applicant, the content of which is hereby specifically incorporated by cross reference.

The aforementioned patent specifications disclose a camera system, hereinafter known as an "Artcam" type camera, wherein sensed images can be directly printed out by an internal Artcam portable camera unit. Further, the aforementioned specification discloses means and methods for performing various manipulations on images captured by the camera sensing device leading to the production of various effects in any output image. The manipulations are disclosed to be highly flexible in nature and can be implemented through the insertion into the ART34US

Artcam of cards having encoded thereon various instructions for the manipulation of images, the cards hereinafter being known as "Artcards". The Artcam further has significant onboard processing power by an Artcam Central Processor unit (ACP) which is interconnected to a memory device for the storage of important data and images.

5 In the preferred embodiment, the Artcam device is modified so as to include a two dimensional motion sensor. The motion sensor can comprise a small micro-electro mechanical system (MEMS) device or other suitable device ~~leave~~able to detect motion in two axes. The motion sensor can be mounted on the camera device and its output monitored by the Artcam central processor device which is disclosed in the afore-mentioned patent specifications.

10 Turning now to Fig. 1, there is illustrated a schematic of the preferred arrangement of the preferred embodiment. The accelerometer 1 outputs to the Artcard processor 2 which also receives the blurred sensed image from the CCD device. The Artcard processor 2 utilises the accelerometer readings so as to determine a likely angular velocity of the camera when the picture was taken. This velocity factor is then utilised by a suitably programmed Artcard  
15 processor 2 to apply a deblurring function to the blurred sensed image 3 thereby outputting a deblurred output image 4. The programming of the Artcard processor 2 so as to perform the deblurring can utilise standard algorithms known to those skilled in the art of computer programming and digital image restoration. For example, reference is made to the "Selected  
20 Papers on Digital Image Restoration", M. Ibrahim Sezan, Editor, SPIE Milestone series, volume 74, and in particular the reprinted paper at pages 167-175 thereof. Further, simplified techniques are shown in the "Image Processing Handbook", second edition, by John C. Russ, published by CRC Press at pages 336-341 thereof.

It would be therefore obvious to the person skilled in the art that many different techniques for motion blur removal can be utilised in the preferred embodiment. Additionally,  
25 other forms of motion sensors may be provided. Once the input image has been deblurred, the image is then able to be printed out by the Artcam device in accordance with the techniques as discussed in the afore-mentioned patent specification.

It would be appreciated by a person skilled in the art that numerous variations and/or modifications may be made to the present invention as shown in the specific embodiment  
30 without departing from the spirit or scope of the invention as broadly described. The present embodiment is, therefore, to be considered in all respects to be illustrative and not restrictive.

#### Ink Jet Technologies

The embodiments of the invention use an ink jet printer type device. Of course many



different devices could be used. However presently popular ink jet printing technologies are unlikely to be suitable.

The most significant problem with thermal inkjet is power consumption. This is approximately 100 times that required for high speed, and stems from the energy-inefficient means of drop ejection. This involves the rapid boiling of water to produce a vapor bubble which expels the ink. Water has a very high heat capacity, and must be superheated in thermal inkjet applications. This leads to an efficiency of around 0.02%, from electricity input to drop momentum (and increased surface area) out.

The most significant problem with piezoelectric inkjet is size and cost. Piezoelectric crystals have a very small deflection at reasonable drive voltages, and therefore require a large area for each nozzle. Also, each piezoelectric actuator must be connected to its drive circuit on a separate substrate. This is not a significant problem at the current limit of around 300 nozzles per print head, but is a major impediment to the fabrication of ~~pagewide~~ pagewidth print heads with 19,200 nozzles.

Ideally, the inkjet technologies used meet the stringent requirements of in-camera digital color printing and other high quality, high speed, low cost printing applications. To meet the requirements of digital photography, new inkjet technologies have been created. The target features include:

- low power (less than 10 Watts)
- high resolution capability (1,600 dpi or more)
- photographic quality output
- low manufacturing cost
- small size (pagewidth times minimum cross section)
- high speed (< 2 seconds per page).

All of these features can be met or exceeded by the inkjet systems described below with differing levels of difficulty. ~~45~~ Forty-five different inkjet technologies have been developed by the Assignee to give a wide range of choices for high volume manufacture. These technologies form part of separate applications assigned to the present Assignee as set out in the table ~~below~~ under the heading "Cross References to Related Applications".

The inkjet designs shown here are suitable for a wide range of digital printing systems, from battery powered one-time use digital cameras, through to desktop and network printers, and through to commercial printing systems.

For ease of manufacture using standard process equipment, the printhead is designed to

ART34US

be a monolithic 0.5 micron CMOS chip with MEMS post processing. For color photographic applications, the printhead is 100 mm long, with a width which depends upon the inkjet type. The smallest printhead designed is IJ38, which is 0.35 mm wide, giving a chip area of 35 square mm. The printheads each contain 19,200 nozzles plus data and control circuitry.

5        Ink is supplied to the back of the printhead by injection molded plastic ink channels. The molding requires 50 micron features, which can be created using a lithographically micromachined insert in a standard injection molding tool. Ink flows through holes etched through the wafer to the nozzle chambers fabricated on the front surface of the wafer. The printhead is connected to the camera circuitry by tape automated bonding.

#### 10    Tables of Drop-on-Demand Inkjets

Eleven important characteristics of the fundamental operation of individual inkjet nozzles have been identified. These characteristics are largely orthogonal, and so can be elucidated as an eleven dimensional matrix. Most of the eleven axes of this matrix include entries developed by the present assignee.

15        The following tables form the axes of an eleven dimensional table of inkjet types.

Actuator mechanism (18 types)

Basic operation mode (7 types)

Auxiliary mechanism (8 types)

Actuator amplification or modification method (17 types)

20        Actuator motion (19 types)

Nozzle refill method (4 types)

Method of restricting back-flow through inlet (10 types)

Nozzle clearing method (9 types)

Nozzle plate construction (9 types)

25        Drop ejection direction (5 types)

Ink type (7 types)

The complete eleven dimensional table represented by these axes contains 36.9 billion possible configurations of inkjet nozzle. While not all of the possible combinations result in a viable inkjet technology, many million configurations are viable. It is clearly impractical to  
30        elucidate all of the possible configurations. Instead, certain inkjet types have been investigated in detail. These are designated IJ01 to IJ45 which match the docket numbers in the table under the heading Cross References to Related Applications.

Other inkjet configurations can readily be derived from these forty-five examples by substituting alternative configurations along one or more of the 11 axes. Most of the IJ01 to  
ART34US

IJ45 examples can be made into inkjet printheads with characteristics superior to any currently available inkjet technology.

5        Where there are prior art examples known to the inventor, one or more of these examples are listed in the examples column of the tables below. The IJ01 to IJ45 series are also listed in the examples column. In some cases, print technology may be listed more than once in a table, where it shares characteristics with more than one entry.

10       Suitable applications include: Home printers, Office network printers, Short run digital printers, Commercial print systems, Fabric printers, Pocket printers, Internet WWW printers, Video printers, Medical imaging, Wide format printers, Notebook PC printers, Fax machines, Industrial printing systems, Photocopiers, Photographic minilabs etc.

The information associated with the aforementioned 11 dimensional matrix are set out in the following tables.

Cross-Referenced Applications

The following table is a guide to cross-referenced patent applications filed concurrently herewith and discussed hereinafter with the reference being utilized in subsequent tables when referring to a particular case:

<b>Docket No.</b>	<b>Reference</b>	<b>Title</b>
IJ01US	IJ01	Radiant Plunger Ink Jet Printer
IJ02US	IJ02	Electrostatic Ink Jet Printer
IJ03US	IJ03	Planar Thermoelastic Bend Actuator Ink Jet
IJ04US	IJ04	Stacked Electrostatic Ink Jet Printer
IJ05US	IJ05	Reverse Spring Lever Ink Jet Printer
IJ06US	IJ06	Paddle Type Ink Jet Printer
IJ07US	IJ07	Permanent Magnet Electromagnetic Ink Jet Printer
IJ08US	IJ08	Planar Swing Grill Electromagnetic Ink Jet Printer
IJ09US	IJ09	Pump Action Refill Ink Jet Printer
IJ10US	IJ10	Pulsed Magnetic Field Ink Jet Printer
IJ11US	IJ11	Two Plate Reverse Firing Electromagnetic Ink Jet Printer
IJ12US	IJ12	Linear Stepper Actuator Ink Jet Printer
IJ13US	IJ13	Gear Driven Shutter Ink Jet Printer
IJ14US	IJ14	Tapered Magnetic Pole Electromagnetic Ink Jet Printer
IJ15US	IJ15	Linear Spring Electromagnetic Grill Ink Jet Printer
IJ16US	IJ16	Lorenz Diaphragm Electromagnetic Ink Jet Printer
IJ17US	IJ17	PTFE Surface Shooting Shuttered Oscillating Pressure Ink Jet Printer
IJ18US	IJ18	Buckle Grip Oscillating Pressure Ink Jet Printer
IJ19US	IJ19	Shutter Based Ink Jet Printer
IJ20US	IJ20	Curling Calyx Thermoelastic Ink Jet Printer
IJ21US	IJ21	Thermal Actuated Ink Jet Printer
IJ22US	IJ22	Iris Motion Ink Jet Printer
IJ23US	IJ23	Direct Firing Thermal Bend Actuator Ink Jet Printer
IJ24US	IJ24	Conductive PTFE Ben Activator Vented Ink Jet Printer
IJ25US	IJ25	Magnetostrictive Ink Jet Printer
IJ26US	IJ26	Shape Memory Alloy Ink Jet Printer
IJ27US	IJ27	Buckle Plate Ink Jet Printer
IJ28US	IJ28	Thermal Elastic Rotary Impeller Ink Jet Printer
IJ29US	IJ29	Thermoelastic Bend Actuator Ink Jet Printer
IJ30US	IJ30	Thermoelastic Bend Actuator Using PTFE and Corrugated Copper Ink Jet Printer
IJ31US	IJ31	Bend Actuator Direct Ink Supply Ink Jet Printer
IJ32US	IJ32	A High Young's Modulus Thermoelastic Ink Jet Printer
IJ33US	IJ33	Thermally actuated slotted chamber wall ink jet printer
IJ34US	IJ34	Ink Jet Printer having a thermal actuator comprising an external coiled spring
IJ35US	IJ35	Trough Container Ink Jet Printer
IJ36US	IJ36	Dual Chamber Single Vertical Actuator Ink Jet
IJ37US	IJ37	Dual Nozzle Single Horizontal Fulerum Actuator Ink Jet

IJ38US	IJ38	Dual Nozzle Single Horizontal Actuator Ink Jet
IJ39US	IJ39	A single bend actuator cupped paddle ink jet printing device
IJ40US	IJ40	A thermally actuated ink jet printer having a series of thermal actuator units
IJ41US	IJ41	A thermally actuated ink jet printer including a tapered heater element
IJ42US	IJ42	Radial Back Curling Thermoelastic Ink Jet
IJ43US	IJ43	Inverted Radial Back Curling Thermoelastic Ink Jet
IJ44US	IJ44	Surface bend actuator vented ink supply ink jet printer
IJ45US	IJ45	Coil Actuated Magnetic Plate Ink Jet Printer

#### Tables of Drop-on Demand Inkjets

Eleven important characteristics of the fundamental operation of individual inkjet nozzles have been identified. These characteristics are largely orthogonal, and so can be elucidated as an eleven dimensional matrix. Most of the eleven axes of this matrix include entries developed by the present assignee.

The following tables form the axes of an eleven dimensional table of inkjet types:

Actuator mechanism (18 types)

Basic operation mode (7 types)

Auxiliary mechanism (8 types)

Actuator amplification or modification method (17 types)

Actuator motion (19 types)

Nozzle refill method (4 types)

Method of restricting back flow through inlet (10 types)

Nozzle clearing method (9 types)

Nozzle plate construction (9 types)

Drop ejection direction (5 types)

Ink type (7 types)

The complete eleven dimensional table represented by these axes contains 36.9 billion possible configurations of inkjet nozzle. While not all of the possible combinations result in a viable inkjet technology, many million configurations are viable. It is clearly impractical to elucidate all of the possible configurations. Instead, certain inkjet types have been investigated in detail. These are designated IJ01 to IJ45 above.

Other inkjet configurations can readily be derived from these 45 examples by substituting alternative configurations along one or more of the 11 axes. Most of the IJ01 to IJ45 examples can be made into inkjet printheads with characteristics superior to any currently

ART34US

available inkjet technology.

5 ~~Where there are prior art examples known to the inventor, one or more of these examples are listed in the examples column of the tables below. The IJ01 to IJ45 series are also listed in the examples column. In some cases, a printer may be listed more than once in a table, where it shares characteristics with more than one entry.~~

~~Suitable applications include: Home printers, Office network printers, Short run digital printers, Commercial print systems, Fabric printers, Pocket printers, Internet WWW printers, Video printers, Medical imaging, Wide format printers, Notebook PC printers, Fax machines, Industrial printing systems, Photocopiers, Photographic minilabs etc.~~

10 ~~The information associated with the aforementioned 11 dimensional matrix are set out in the following tables.~~

**ACTUATOR MECHANISM (APPLIED ONLY TO SELECTED INK DROPS)**

<b>Actuator Mechanism</b>	<b>Description</b>	<b>Advantages</b>	<b>Disadvantages</b>	<b>Examples</b>
<b>Thermal bubble</b>	<p>An electrothermal heater heats the ink to above boiling point, transferring significant heat to the aqueous ink. A bubble nucleates and quickly forms, expelling the ink.</p> <p>The efficiency of the process is low, with typically less than 0.05% of the electrical energy being transformed into kinetic energy of the drop.</p>	<ul style="list-style-type: none"> <li>◆ Large force generated</li> <li>◆ Simple construction</li> <li>◆ No moving parts</li> <li>◆ Fast operation</li> <li>◆ Small chip area required for actuator</li> </ul>	<ul style="list-style-type: none"> <li>◆ High power</li> <li>◆ Ink carrier limited to water</li> <li>◆ Low efficiency</li> <li>◆ High temperatures required</li> <li>◆ High mechanical stress</li> <li>◆ Unusual materials required</li> <li>◆ Large drive transistors</li> <li>◆ Cavitation causes actuator failure</li> <li>◆ Kogation reduces bubble formation</li> <li>◆ Large print heads are difficult to fabricate</li> </ul>	<ul style="list-style-type: none"> <li>◆ Canon Bubblejet 1979 Endo et al GB patent 2,007,162</li> <li>◆ Xerox heater-in-pit 1990 Hawkins et al USP 4,899,181</li> <li>◆ Hewlett-Packard TIJ 1982 Vaught et al USP 4,490,728</li> </ul>
<b>Piezoelectric</b>	<p>A piezoelectric crystal such as lead lanthanum zirconate (PZT) is electrically activated, and either expands, shears, or bends to apply pressure to the ink, ejecting drops.</p>	<ul style="list-style-type: none"> <li>◆ Low power consumption</li> <li>◆ Many ink types can be used</li> <li>◆ Fast operation</li> <li>◆ High efficiency</li> </ul>	<ul style="list-style-type: none"> <li>◆ Very large area required for actuator</li> <li>◆ Difficult to integrate with electronics</li> <li>◆ High voltage drive transistors required</li> <li>◆ Full pagewidth print heads impractical due to actuator size</li> <li>◆ Requires electrical poling in high field strengths during manufacture</li> </ul>	<ul style="list-style-type: none"> <li>◆ Kyser et al USP 3,946,398</li> <li>◆ Zoltan USP 3,683,212</li> <li>◆ 1973 Stemme USP 3,747,120</li> <li>◆ Epson Stylus</li> <li>◆ Tektronix</li> <li>◆ IJ04</li> </ul>
<b>Electrostrictive</b>	<p>An electric field is used to activate electrostriction in relaxor materials such as lead lanthanum zirconate titanate (PLZT) or lead magnesium niobate (PMN).</p>	<ul style="list-style-type: none"> <li>◆ Low power consumption</li> <li>◆ Many ink types can be used</li> <li>◆ Low thermal expansion</li> <li>◆ Electric field strength required (approx. 3.5 V/μm) can be generated without difficulty</li> <li>◆ Does not require electrical poling</li> </ul>	<ul style="list-style-type: none"> <li>◆ Low maximum strain (approx. 0.01%)</li> <li>◆ Large area required for actuator due to low strain</li> <li>◆ Response speed is marginal (~ 10 μs)</li> <li>◆ High voltage drive transistors required</li> <li>◆ Full pagewidth print heads impractical due to actuator size</li> </ul>	<ul style="list-style-type: none"> <li>◆ Seiko Epson, Usui et al JP 253401/96</li> <li>◆ IJ04</li> </ul>

<b>Ferroelectric</b>	An electric field is used to induce a phase transition between the antiferroelectric (AFE) and ferroelectric (FE) phase. Perovskite materials such as tin modified lead lanthanum zirconate titanate (PLZSnT) exhibit large strains of up to 1% associated with the AFE to FE phase transition.	<ul style="list-style-type: none"> <li>◆ Low power consumption</li> <li>◆ Many ink types can be used</li> <li>◆ Fast operation (<math>&lt; 1 \mu\text{s}</math>)</li> <li>◆ Relatively high longitudinal strain</li> <li>◆ High efficiency</li> <li>◆ Electric field strength of around <math>3 \text{ V}/\mu\text{m}</math> can be readily provided</li> </ul>	<ul style="list-style-type: none"> <li>◆ Difficult to integrate with electronics</li> <li>◆ Unusual materials such as PLZSnT are required</li> <li>◆ Actuators require a large area</li> <li>◆</li> </ul>	◆ IJ04
<b>Electrostatic plates</b>	Conductive plates are separated by a compressible or fluid dielectric (usually air). Upon application of a voltage, the plates attract each other and displace ink, causing drop ejection. The conductive plates may be in a comb or honeycomb structure, or stacked to increase the surface area and therefore the force.	<ul style="list-style-type: none"> <li>◆ Low power consumption</li> <li>◆ Many ink types can be used</li> <li>◆ Fast operation</li> </ul>	<ul style="list-style-type: none"> <li>◆ Difficult to operate electrostatic devices in an aqueous environment</li> <li>◆ The electrostatic actuator will normally need to be separated from the ink</li> <li>◆ Very large area required to achieve high forces</li> <li>◆ High voltage drive transistors may be required</li> <li>◆ Full pagewidth print heads are not competitive due to actuator size</li> </ul>	◆ IJ02, IJ04
<b>Electrostatic pull on ink</b>	A strong electric field is applied to the ink, whereupon electrostatic attraction accelerates the ink towards the print medium.	<ul style="list-style-type: none"> <li>◆ Low current consumption</li> <li>◆ Low temperature</li> </ul>	<ul style="list-style-type: none"> <li>◆ High voltage required</li> <li>◆ May be damaged by sparks due to air breakdown</li> <li>◆ Required field strength increases as the drop size decreases</li> <li>◆ High voltage drive transistors required</li> <li>◆ Electrostatic field attracts dust</li> </ul>	<ul style="list-style-type: none"> <li>◆ 1989 Saito et al, USP 4,799,068</li> <li>◆ 1989 Miura et al, USP 4,810,954</li> <li>◆ Tone-jet</li> </ul>



<b>Permanent magnet electro-magnetic</b>	An electromagnet directly attracts a permanent magnet, displacing ink and causing drop ejection. Rare earth magnets with a field strength around 1 Tesla can be used. Examples are: Samarium Cobalt (SaCo) and magnetic materials in the neodymium iron boron family (NdFeB, NdDyFeBNb, NdDyFeB, etc)	<ul style="list-style-type: none"> <li>◆ Low power consumption</li> <li>◆ Many ink types can be used</li> <li>◆ Fast operation</li> <li>◆ High efficiency</li> <li>◆ Easy extension from single nozzles to pagewidth print heads</li> </ul>	<ul style="list-style-type: none"> <li>◆ Complex fabrication</li> <li>◆ Permanent magnetic material such as Neodymium Iron Boron (NdFeB) required.</li> <li>◆ High local currents required</li> <li>◆ Copper metalization should be used for long electromigration lifetime and low resistivity</li> <li>◆ Pigmented inks are usually infeasible</li> <li>◆ Operating temperature limited to the Curie temperature (around 540 K)</li> </ul>	◆ IJ07, IJ10
<b>Soft magnetic core electro-magnetic</b>	A solenoid induced a magnetic field in a soft magnetic core or yoke fabricated from a ferrous material such as electroplated iron alloys such as CoNiFe [1], CoFe, or NiFe alloys. Typically, the soft magnetic material is in two parts, which are normally held apart by a spring. When the solenoid is actuated, the two parts attract, displacing the ink.	<ul style="list-style-type: none"> <li>◆ Low power consumption</li> <li>◆ Many ink types can be used</li> <li>◆ Fast operation</li> <li>◆ High efficiency</li> <li>◆ Easy extension from single nozzles to pagewidth print heads</li> <li>◆</li> </ul>	<ul style="list-style-type: none"> <li>◆ Complex fabrication</li> <li>◆ Materials not usually present in a CMOS fab such as NiFe, CoNiFe, or CoFe are required</li> <li>◆ High local currents required</li> <li>◆ Copper metalization should be used for long electromigration lifetime and low resistivity</li> <li>◆ Electroplating is required</li> <li>◆ High saturation flux density is required (2.0-2.1 T is achievable with CoNiFe [1])</li> </ul>	◆ IJ01, IJ05, IJ08, IJ10 ◆ IJ12, IJ14, IJ15, IJ17 ◆
<b>Magnetic Lorentz force</b>	The Lorentz force acting on a current carrying wire in a magnetic field is utilized. This allows the magnetic field to be supplied externally to the print head, for example with rare earth permanent magnets. Only the current carrying wire need be fabricated on the print-head, simplifying materials requirements.	<ul style="list-style-type: none"> <li>◆ Low power consumption</li> <li>◆ Many ink types can be used</li> <li>◆ Fast operation</li> <li>◆ High efficiency</li> <li>◆ Easy extension from single nozzles to pagewidth print heads</li> </ul>	<ul style="list-style-type: none"> <li>◆ Force acts as a twisting motion</li> <li>◆ Typically, only a quarter of the solenoid length provides force in a useful direction</li> <li>◆ High local currents required</li> <li>◆ Copper metalization should be used for long electromigration lifetime and low resistivity</li> <li>◆ Pigmented inks are usually infeasible</li> </ul>	◆ IJ06, IJ11, IJ13, IJ16 ◆

<b>Magnetostriction</b>	The actuator uses the giant magnetostrictive effect of materials such as Terfenol-D (an alloy of terbium, dysprosium and iron developed at the Naval Ordnance Laboratory, hence Ter-Fe-NOL). For best efficiency, the actuator should be pre-stressed to approx. 8 MPa.	<ul style="list-style-type: none"> <li>◆ Many ink types can be used</li> <li>◆ Fast operation</li> <li>◆ Easy extension from single nozzles to pagewidth print heads</li> <li>◆ High force is available</li> </ul>	<ul style="list-style-type: none"> <li>◆ Force acts as a twisting motion</li> <li>◆ Unusual materials such as Terfenol-D are required</li> <li>◆ High local currents required</li> <li>◆ Copper metalization should be used for long electromigration lifetime and low resistivity</li> <li>◆ Pre-stressing may be required</li> </ul>	<ul style="list-style-type: none"> <li>◆ Fischenbeck, USP 4,032,929</li> <li>◆ IJ25</li> </ul>
<b>Surface tension reduction</b>	Ink under positive pressure is held in a nozzle by surface tension. The surface tension of the ink is reduced below the bubble threshold, causing the ink to egress from the nozzle.	<ul style="list-style-type: none"> <li>◆ Low power consumption</li> <li>◆ Simple construction</li> <li>◆ No unusual materials required in fabrication</li> <li>◆ High efficiency</li> <li>◆ Easy extension from single nozzles to pagewidth print heads</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires supplementary force to effect drop separation</li> <li>◆ Requires special ink surfactants</li> <li>◆ Speed may be limited by surfactant properties</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> </ul>
<b>Viscosity reduction</b>	The ink viscosity is locally reduced to select which drops are to be ejected. A viscosity reduction can be achieved electrothermally with most inks, but special inks can be engineered for a 100:1 viscosity reduction.	<ul style="list-style-type: none"> <li>◆ Simple construction</li> <li>◆ No unusual materials required in fabrication</li> <li>◆ Easy extension from single nozzles to pagewidth print heads</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires supplementary force to effect drop separation</li> <li>◆ Requires special ink viscosity properties</li> <li>◆ High speed is difficult to achieve</li> <li>◆ Requires oscillating ink pressure</li> <li>◆ A high temperature difference (typically 80 degrees) is required</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> </ul>
<b>Acoustic</b>	An acoustic wave is generated and focussed upon the drop ejection region.	<ul style="list-style-type: none"> <li>◆ Can operate without a nozzle plate</li> <li>◆</li> </ul>	<ul style="list-style-type: none"> <li>◆ Complex drive circuitry</li> <li>◆ Complex fabrication</li> <li>◆ Low efficiency</li> <li>◆ Poor control of drop position</li> <li>◆ Poor control of drop volume</li> </ul>	<ul style="list-style-type: none"> <li>◆ 1993 Hadimioglu et al, EUP 550,192</li> <li>◆ 1993 Elrod et al, EUP 572,220</li> </ul>

<b>Thermoelastic bend actuator</b>	An actuator which relies upon differential thermal expansion upon Joule heating is used.	<ul style="list-style-type: none"> <li>◆ Low power consumption</li> <li>◆ Many ink types can be used</li> <li>◆ Simple planar fabrication</li> <li>◆ Small chip area required for each actuator</li> <li>◆ Fast operation</li> <li>◆ High efficiency</li> <li>◆ CMOS compatible voltages and currents</li> <li>◆ Standard MEMS processes can be used</li> <li>◆ Easy extension from single nozzles to pagewidth print heads</li> </ul>	<ul style="list-style-type: none"> <li>◆ Efficient aqueous operation requires a thermal insulator on the hot side</li> <li>◆ Corrosion prevention can be difficult</li> <li>◆ Pigmented inks may be infeasible, as pigment particles may jam the bend actuator</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ03, IJ09, IJ17, IJ18</li> <li>◆ IJ19, IJ20, IJ21, IJ22</li> <li>◆ IJ23, IJ24, IJ27, IJ28</li> <li>◆ IJ29, IJ30, IJ31, IJ32</li> <li>◆ IJ33, IJ34, IJ35, IJ36</li> <li>◆ IJ37, IJ38, IJ39, IJ40</li> <li>◆ IJ41</li> <li>◆</li> </ul>
<b>High CTE thermoelastic actuator</b>	<p>A material with a very high coefficient of thermal expansion (CTE) such as polytetrafluoroethylene (PTFE) is used. As high CTE materials are usually non-conductive, a heater fabricated from a conductive material is incorporated. A 50 <math>\mu\text{m}</math> long PTFE bend actuator with polysilicon heater and 15 mW power input can provide 180 <math>\mu\text{N}</math> force and 10 <math>\mu\text{m}</math> deflection. Actuator motions include:</p> <ol style="list-style-type: none"> <li>1) Bend</li> <li>2) Push</li> <li>3) Buckle</li> <li>4) Rotate</li> </ol>	<ul style="list-style-type: none"> <li>◆ High force can be generated</li> <li>◆ PTFE is a candidate for low dielectric constant insulation in ULSI</li> <li>◆ Very low power consumption</li> <li>◆ Many ink types can be used</li> <li>◆ Simple planar fabrication</li> <li>◆ Small chip area required for each actuator</li> <li>◆ Fast operation</li> <li>◆ High efficiency</li> <li>◆ CMOS compatible voltages and currents</li> <li>◆ Easy extension from single nozzles to pagewidth print heads</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires special material (e.g. PTFE)</li> <li>◆ Requires a PTFE deposition process, which is not yet standard in ULSI fabs</li> <li>◆ PTFE deposition cannot be followed with high temperature (above 350 °C) processing</li> <li>◆ Pigmented inks may be infeasible, as pigment particles may jam the bend actuator</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ09, IJ17, IJ18, IJ20</li> <li>◆ IJ21, IJ22, IJ23, IJ24</li> <li>◆ IJ27, IJ28, IJ29, IJ30</li> <li>◆ IJ31, IJ42, IJ43, IJ44</li> </ul>

<b>Conductive polymer thermoelastic actuator</b>	<p>A polymer with a high coefficient of thermal expansion (such as PTFE) is doped with conducting substances to increase its conductivity to about 3 orders of magnitude below that of copper. The conducting polymer expands when resistively heated.</p> <p>Examples of conducting dopants include:</p> <ol style="list-style-type: none"> <li>1) Carbon nanotubes</li> <li>2) Metal fibers</li> <li>3) Conductive polymers such as doped polythiophene</li> <li>4) Carbon granules</li> </ol>	<ul style="list-style-type: none"> <li>◆ High force can be generated</li> <li>◆ Very low power consumption</li> <li>◆ Many ink types can be used</li> <li>◆ Simple planar fabrication</li> <li>◆ Small chip area required for each actuator</li> <li>◆ Fast operation</li> <li>◆ High efficiency</li> <li>◆ CMOS compatible voltages and currents</li> <li>◆ Easy extension from single nozzles to pagewidth print heads</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires special materials development (High CTE conductive polymer)</li> <li>◆ Requires a PTFE deposition process, which is not yet standard in ULSI fabs</li> <li>◆ PTFE deposition cannot be followed with high temperature (above 350 °C) processing</li> <li>◆ Evaporation and CVD deposition techniques cannot be used</li> <li>◆ Pigmented inks may be infeasible, as pigment particles may jam the bend actuator</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ24</li> </ul>
<b>Shape memory alloy</b>	<p>A shape memory alloy such as TiNi (also known as Nitinol - Nickel Titanium alloy developed at the Naval Ordnance Laboratory) is thermally switched between its weak martensitic state and its high stiffness austenitic state. The shape of the actuator in its martensitic state is deformed relative to the austenitic shape. The shape change causes ejection of a drop.</p>	<ul style="list-style-type: none"> <li>◆ High force is available (stresses of hundreds of MPa)</li> <li>◆ Large strain is available (more than 3%)</li> <li>◆ High corrosion resistance</li> <li>◆ Simple construction</li> <li>◆ Easy extension from single nozzles to pagewidth print heads</li> <li>◆ Low voltage operation</li> </ul>	<ul style="list-style-type: none"> <li>◆ Fatigue limits maximum number of cycles</li> <li>◆ Low strain (1%) is required to extend fatigue resistance</li> <li>◆ Cycle rate limited by heat removal</li> <li>◆ Requires unusual materials (TiNi)</li> <li>◆ The latent heat of transformation must be provided</li> <li>◆ High current operation</li> <li>◆ Requires pre-stressing to distort the martensitic state</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ26</li> </ul>

<b>Linear Magnetic Actuator</b>	Linear magnetic actuators include the Linear Induction Actuator (LIA), Linear Permanent Magnet Synchronous Actuator (LPMSA), Linear Reluctance Synchronous Actuator (LRSA), Linear Switched Reluctance Actuator (LSRA), and the Linear Stepper Actuator (LSA).	<ul style="list-style-type: none"><li>◆ Linear Magnetic actuators can be constructed with high thrust, long travel, and high efficiency using planar semiconductor fabrication techniques</li><li>◆ Long actuator travel is available</li><li>◆ Medium force is available</li><li>◆ Low voltage operation</li></ul>	<ul style="list-style-type: none"><li>◆ Requires unusual semiconductor materials such as soft magnetic alloys (e.g. CoNiFe [1])</li><li>◆ Some varieties also require permanent magnetic materials such as Neodymium iron boron (NdFeB)</li><li>◆ Requires complex multi-phase drive circuitry</li><li>◆ High current operation</li></ul>	◆ IJ12
---------------------------------	--	---	---	--------

# **BASIC OPERATION MODE**

Operational mode	Description	Advantages	Disadvantages	Examples
<b>Actuator directly pushes ink</b>	This is the simplest mode of operation: the actuator directly supplies sufficient kinetic energy to expel the drop. The drop must have a sufficient velocity to overcome the surface tension.	<ul style="list-style-type: none"> <li>◆ Simple operation</li> <li>◆ No external fields required</li> <li>◆ Satellite drops can be avoided if drop velocity is less than 4 m/s</li> <li>◆ Can be efficient, depending upon the actuator used</li> </ul>	<ul style="list-style-type: none"> <li>◆ Drop repetition rate is usually limited to less than 10 KHz. However, this is not fundamental to the method, but is related to the refill method normally used</li> <li>◆ All of the drop kinetic energy must be provided by the actuator</li> <li>◆ Satellite drops usually form if drop velocity is greater than 4.5 m/s</li> </ul>	<ul style="list-style-type: none"> <li>◆ Thermal inkjet</li> <li>◆ Piezoelectric inkjet</li> <li>◆ IJ01, IJ02, IJ03, IJ04</li> <li>◆ IJ05, IJ06, IJ07, IJ09</li> <li>◆ IJ11, IJ12, IJ14, IJ16</li> <li>◆ IJ20, IJ22, IJ23, IJ24</li> <li>◆ IJ25, IJ26, IJ27, IJ28</li> <li>◆ IJ29, IJ30, IJ31, IJ32</li> <li>◆ IJ33, IJ34, IJ35, IJ36</li> <li>◆ IJ37, IJ38, IJ39, IJ40</li> <li>◆ IJ41, IJ42, IJ43, IJ44</li> </ul>
<b>Proximity</b>	The drops to be printed are selected by some manner (e.g. thermally induced surface tension reduction of pressurized ink). Selected drops are separated from the ink in the nozzle by contact with the print medium or a transfer roller.	<ul style="list-style-type: none"> <li>◆ Very simple print head fabrication can be used</li> <li>◆ The drop selection means does not need to provide the energy required to separate the drop from the nozzle</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires close proximity between the print head and the print media or transfer roller</li> <li>◆ May require two print heads printing alternate rows of the image</li> <li>◆ Monolithic color print heads are difficult</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> </ul>
<b>Electrostatic pull on ink</b>	The drops to be printed are selected by some manner (e.g. thermally induced surface tension reduction of pressurized ink). Selected drops are separated from the ink in the nozzle by a strong electric field.	<ul style="list-style-type: none"> <li>◆ Very simple print head fabrication can be used</li> <li>◆ The drop selection means does not need to provide the energy required to separate the drop from the nozzle</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires very high electrostatic field</li> <li>◆ Electrostatic field for small nozzle sizes is above air breakdown</li> <li>◆ Electrostatic field may attract dust</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> <li>◆ Tone-Jet</li> </ul>

<b>Magnetic pull on ink</b>	The drops to be printed are selected by some manner (e.g. thermally induced surface tension reduction of pressurized ink). Selected drops are separated from the ink in the nozzle by a strong magnetic field acting on the magnetic ink.	<ul style="list-style-type: none"> <li>◆ Very simple print head fabrication can be used</li> <li>◆ The drop selection means does not need to provide the energy required to separate the drop from the nozzle</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires magnetic ink</li> <li>◆ Ink colors other than black are difficult</li> <li>◆ Requires very high magnetic fields</li> </ul>	◆ Silverbrook, EP 0771 658 A2 and related patent applications
<b>Shutter</b>	The actuator moves a shutter to block ink flow to the nozzle. The ink pressure is pulsed at a multiple of the drop ejection frequency.	<ul style="list-style-type: none"> <li>◆ High speed (&gt;50 KHz) operation can be achieved due to reduced refill time</li> <li>◆ Drop timing can be very accurate</li> <li>◆ The actuator energy can be very low</li> </ul>	<ul style="list-style-type: none"> <li>◆ Moving parts are required</li> <li>◆ Requires ink pressure modulator</li> <li>◆ Friction and wear must be considered</li> <li>◆ Stiction is possible</li> </ul>	◆ IJ13, IJ17, IJ21
<b>Shuttered grill</b>	The actuator moves a shutter to block ink flow through a grill to the nozzle. The shutter movement need only be equal to the width of the grill holes.	<ul style="list-style-type: none"> <li>◆ Actuators with small travel can be used</li> <li>◆ Actuators with small force can be used</li> <li>◆ High speed (&gt;50 KHz) operation can be achieved</li> </ul>	<ul style="list-style-type: none"> <li>◆ Moving parts are required</li> <li>◆ Requires ink pressure modulator</li> <li>◆ Friction and wear must be considered</li> <li>◆ Stiction is possible</li> </ul>	◆ IJ08, IJ15, IJ18, IJ19
<b>Pulsed magnetic pull on ink pusher</b>	A pulsed magnetic field attracts an 'ink pusher' at the drop ejection frequency. An actuator controls a catch, which prevents the ink pusher from moving when a drop is not to be ejected.	<ul style="list-style-type: none"> <li>◆ Extremely low energy operation is possible</li> <li>◆ No heat dissipation problems</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires an external pulsed magnetic field</li> <li>◆ Requires special materials for both the actuator and the ink pusher</li> <li>◆ Complex construction</li> </ul>	◆ IJ10

**AUXILIARY MECHANISM (APPLIED TO ALL NOZZLES)**

<b>Auxiliary Mechanism</b>	<b>Description</b>	<b>Advantages</b>	<b>Disadvantages</b>	<b>Examples</b>
<b>None</b>	The actuator directly fires the ink drop, and there is no external field or other mechanism required.	<ul style="list-style-type: none"> <li>◆ Simplicity of construction</li> <li>◆ Simplicity of operation</li> <li>◆ Small physical size</li> </ul>	<ul style="list-style-type: none"> <li>◆ Drop ejection energy must be supplied by individual nozzle actuator</li> </ul>	<ul style="list-style-type: none"> <li>◆ Most inkjets, including piezoelectric and thermal bubble.</li> <li>◆ IJ01- IJ07, IJ09, IJ11</li> <li>◆ IJ12, IJ14, IJ20, IJ22</li> <li>◆ IJ23-IJ45</li> </ul>
<b>Oscillating ink pressure (including acoustic stimulation)</b>	The ink pressure oscillates, providing much of the drop ejection energy. The actuator selects which drops are to be fired by selectively blocking or enabling nozzles. The ink pressure oscillation may be achieved by vibrating the print head, or preferably by an actuator in the ink supply.	<ul style="list-style-type: none"> <li>◆ Oscillating ink pressure can provide a refill pulse, allowing higher operating speed</li> <li>◆ The actuators may operate with much lower energy</li> <li>◆ Acoustic lenses can be used to focus the sound on the nozzles</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires external ink pressure oscillator</li> <li>◆ Ink pressure phase and amplitude must be carefully controlled</li> <li>◆ Acoustic reflections in the ink chamber must be designed for</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> <li>◆ IJ08, IJ13, IJ15, IJ17</li> <li>◆ IJ18, IJ19, IJ21</li> </ul>
<b>Media proximity</b>	The print head is placed in close proximity to the print medium. Selected drops protrude from the print head further than unselected drops, and contact the print medium. The drop soaks into the medium fast enough to cause drop separation.	<ul style="list-style-type: none"> <li>◆ Low power</li> <li>◆ High accuracy</li> <li>◆ Simple print head construction</li> </ul>	<ul style="list-style-type: none"> <li>◆ Precision assembly required</li> <li>◆ Paper fibers may cause problems</li> <li>◆ Cannot print on rough substrates</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> </ul>
<b>Transfer roller</b>	Drops are printed to a transfer roller instead of straight to the print medium. A transfer roller can also be used for proximity drop separation.	<ul style="list-style-type: none"> <li>◆ High accuracy</li> <li>◆ Wide range of print substrates can be used</li> <li>◆ Ink can be dried on the transfer roller</li> </ul>	<ul style="list-style-type: none"> <li>◆ Bulky</li> <li>◆ Expensive</li> <li>◆ Complex construction</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> <li>◆ Tektronix hot melt piezoelectric inkjet</li> <li>◆ Any of the IJ series</li> </ul>
<b>Electrostatic</b>	An electric field is used to accelerate selected drops towards the print medium.	<ul style="list-style-type: none"> <li>◆ Low power</li> <li>◆ Simple print head construction</li> </ul>	<ul style="list-style-type: none"> <li>◆ Field strength required for separation of small drops is near or above air breakdown</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> <li>◆ Tone-Jet</li> </ul>
<b>Direct magnetic field</b>	A magnetic field is used to accelerate selected drops of magnetic ink towards the print medium.	<ul style="list-style-type: none"> <li>◆ Low power</li> <li>◆ Simple print head construction</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires magnetic ink</li> <li>◆ Requires strong magnetic field</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> </ul>
<b>Cross magnetic field</b>	The print head is placed in a constant magnetic field. The Lorentz force in a current carrying wire is used to move the actuator.	<ul style="list-style-type: none"> <li>◆ Does not require magnetic materials to be integrated in the print head manufacturing process</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires external magnet</li> <li>◆ Current densities may be high, resulting in electromigration problems</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ06, IJ16</li> </ul>



<b>Pulsed magnetic field</b>	A pulsed magnetic field is used to cyclically attract a paddle, which pushes on the ink. A small actuator moves a catch, which selectively prevents the paddle from moving.	<ul style="list-style-type: none"><li>◆ Very low power operation is possible</li><li>◆ Small print head size</li></ul>	<ul style="list-style-type: none"><li>◆ Complex print head construction</li><li>◆ Magnetic materials required in print head</li></ul>	<ul style="list-style-type: none"><li>◆ IJ10</li></ul>
------------------------------	---	--	---	--

**ACTUATOR AMPLIFICATION OR MODIFICATION METHOD**

<b>Actuator amplification</b>	<b>Description</b>	<b>Advantages</b>	<b>Disadvantages</b>	<b>Examples</b>
<b>None</b>	No actuator mechanical amplification is used. The actuator directly drives the drop ejection process.	<ul style="list-style-type: none"> <li>◆ Operational simplicity</li> </ul>	<ul style="list-style-type: none"> <li>◆ Many actuator mechanisms have insufficient travel, or insufficient force, to efficiently drive the drop ejection process</li> </ul>	<ul style="list-style-type: none"> <li>◆ Thermal Bubble Inkjet</li> <li>◆ IJ01, IJ02, IJ06, IJ07</li> <li>◆ IJ16, IJ25, IJ26</li> </ul>
<b>Differential expansion bend actuator</b>	An actuator material expands more on one side than on the other. The expansion may be thermal, piezoelectric, magnetostrictive, or other mechanism.	<ul style="list-style-type: none"> <li>◆ Provides greater travel in a reduced print head area</li> <li>◆ The bend actuator converts a high force low travel actuator mechanism to high travel, lower force mechanism.</li> </ul>	<ul style="list-style-type: none"> <li>◆ High stresses are involved</li> <li>◆ Care must be taken that the materials do not delaminate</li> <li>◆ Residual bend resulting from high temperature or high stress during formation</li> </ul>	<ul style="list-style-type: none"> <li>◆ Piezoelectric</li> <li>◆ IJ03, IJ09, IJ17-IJ24</li> <li>◆ IJ27, IJ29-IJ39, IJ42,</li> <li>◆ IJ43, IJ44</li> </ul>
<b>Transient bend actuator</b>	A trilayer bend actuator where the two outside layers are identical. This cancels bend due to ambient temperature and residual stress. The actuator only responds to transient heating of one side or the other.	<ul style="list-style-type: none"> <li>◆ Very good temperature stability</li> <li>◆ High speed, as a new drop can be fired before heat dissipates</li> <li>◆ Cancels residual stress of formation</li> </ul>	<ul style="list-style-type: none"> <li>◆ High stresses are involved</li> <li>◆ Care must be taken that the materials do not delaminate</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ40, IJ41</li> </ul>
<b>Actuator stack</b>	A series of thin actuators are stacked. This can be appropriate where actuators require high electric field strength, such as electrostatic and piezoelectric actuators.	<ul style="list-style-type: none"> <li>◆ Increased travel</li> <li>◆ Reduced drive voltage</li> </ul>	<ul style="list-style-type: none"> <li>◆ Increased fabrication complexity</li> <li>◆ Increased possibility of short circuits due to pinholes</li> </ul>	<ul style="list-style-type: none"> <li>◆ Some piezoelectric ink jets</li> <li>◆ IJ04</li> </ul>
<b>Multiple actuators</b>	Multiple smaller actuators are used simultaneously to move the ink. Each actuator need provide only a portion of the force required.	<ul style="list-style-type: none"> <li>◆ Increases the force available from an actuator</li> <li>◆ Multiple actuators can be positioned to control ink flow accurately</li> </ul>	<ul style="list-style-type: none"> <li>◆ Actuator forces may not add linearly, reducing efficiency</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ12, IJ13, IJ18, IJ20</li> <li>◆ IJ22, IJ28, IJ42, IJ43</li> </ul>
<b>Linear Spring</b>	A linear spring is used to transform a motion with small travel and high force into a longer travel, lower force motion.	<ul style="list-style-type: none"> <li>◆ Matches low travel actuator with higher travel requirements</li> <li>◆ Non-contact method of motion transformation</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires print head area for the spring</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ15</li> </ul>

<b>Reverse spring</b>	The actuator loads a spring. When the actuator is turned off, the spring releases. This can reverse the force/distance curve of the actuator to make it compatible with the force/time requirements of the drop ejection.	<ul style="list-style-type: none"> <li>◆ Better coupling to the ink</li> </ul>	<ul style="list-style-type: none"> <li>◆ Fabrication complexity</li> <li>◆ High stress in the spring</li> </ul>	◆ IJ05, IJ11
<b>Coiled actuator</b>	A bend actuator is coiled to provide greater travel in a reduced chip area.	<ul style="list-style-type: none"> <li>◆ Increases travel</li> <li>◆ Reduces chip area</li> <li>◆ Planar implementations are relatively easy to fabricate.</li> </ul>	<ul style="list-style-type: none"> <li>◆ Generally restricted to planar implementations due to extreme fabrication difficulty in other orientations.</li> </ul>	◆ IJ17, IJ21, IJ34, IJ35
<b>Flexure bend actuator</b>	A bend actuator has a small region near the fixture point, which flexes much more readily than the remainder of the actuator. The actuator flexing is effectively converted from an even coiling to an angular bend, resulting in greater travel of the actuator tip.	<ul style="list-style-type: none"> <li>◆ Simple means of increasing travel of a bend actuator</li> </ul>	<ul style="list-style-type: none"> <li>◆ Care must be taken not to exceed the elastic limit in the flexure area</li> <li>◆ Stress distribution is very uneven</li> <li>◆ Difficult to accurately model with finite element analysis</li> </ul>	◆ IJ10, IJ19, IJ33
<b>Gears</b>	Gears can be used to increase travel at the expense of duration. Circular gears, rack and pinion, ratchets, and other gearing methods can be used.	<ul style="list-style-type: none"> <li>◆ Low force, low travel actuators can be used</li> <li>◆ Can be fabricated using standard surface MEMS processes</li> </ul>	<ul style="list-style-type: none"> <li>◆ Moving parts are required</li> <li>◆ Several actuator cycles are required</li> <li>◆ More complex drive electronics</li> <li>◆ Complex construction</li> <li>◆ Friction, friction, and wear are possible</li> </ul>	◆ IJ13
<b>Catch</b>	The actuator controls a small catch. The catch either enables or disables movement of an ink pusher that is controlled in a bulk manner.	<ul style="list-style-type: none"> <li>◆ Very low actuator energy</li> <li>◆ Very small actuator size</li> </ul>	<ul style="list-style-type: none"> <li>◆ Complex construction</li> <li>◆ Requires external force</li> <li>◆ Unsuitable for pigmented inks</li> </ul>	◆ IJ10
<b>Buckle plate</b>	A buckle plate can be used to change a slow actuator into a fast motion. It can also convert a high force, low travel actuator into a high travel, medium force motion.	<ul style="list-style-type: none"> <li>◆ Very fast movement achievable</li> </ul>	<ul style="list-style-type: none"> <li>◆ Must stay within elastic limits of the materials for long device life</li> <li>◆ High stresses involved</li> <li>◆ Generally high power requirement</li> </ul>	<ul style="list-style-type: none"> <li>◆ S. Hirata et al, "An Ink-jet Head ...", Proc. IEEE MEMS, Feb. 1996, pp 418-423.</li> <li>◆ IJ18, IJ27</li> </ul>
<b>Tapered magnetic pole</b>	A tapered magnetic pole can increase travel at the expense of force.	<ul style="list-style-type: none"> <li>◆ Linearizes the magnetic force/distance curve</li> </ul>	<ul style="list-style-type: none"> <li>◆ Complex construction</li> </ul>	◆ IJ14

<b>Lever</b>	A lever and fulcrum is used to transform a motion with small travel and high force into a motion with longer travel and lower force. The lever can also reverse the direction of travel.	<ul style="list-style-type: none"> <li>◆ Matches low travel actuator with higher travel requirements</li> <li>◆ Fulcrum area has no linear movement, and can be used for a fluid seal</li> </ul>	<ul style="list-style-type: none"> <li>◆ High stress around the fulcrum</li> </ul>	◆ IJ32, IJ36, IJ37
<b>Rotary impeller</b>	The actuator is connected to a rotary impeller. A small angular deflection of the actuator results in a rotation of the impeller vanes, which push the ink against stationary vanes and out of the nozzle.	<ul style="list-style-type: none"> <li>◆ High mechanical advantage</li> <li>◆ The ratio of force to travel of the actuator can be matched to the nozzle requirements by varying the number of impeller vanes</li> </ul>	<ul style="list-style-type: none"> <li>◆ Complex construction</li> <li>◆ Unsuitable for pigmented inks</li> </ul>	◆ IJ28
<b>Acoustic lens</b>	A refractive or diffractive (e.g. zone plate) acoustic lens is used to concentrate sound waves.	<ul style="list-style-type: none"> <li>◆ No moving parts</li> </ul>	<ul style="list-style-type: none"> <li>◆ Large area required</li> <li>◆ Only relevant for acoustic ink jets</li> </ul>	<ul style="list-style-type: none"> <li>◆ 1993 Hadimioglu et al, EUP 550,192</li> <li>◆ 1993 Elrod et al, EUP 572,220</li> </ul>
<b>Sharp conductive point</b>	A sharp point is used to concentrate an electrostatic field.	<ul style="list-style-type: none"> <li>◆ Simple construction</li> </ul>	<ul style="list-style-type: none"> <li>◆ Difficult to fabricate using standard VLSI processes for a surface ejecting ink-jet</li> <li>◆ Only relevant for electrostatic ink jets</li> </ul>	◆ Tone-jet

# ACTUATOR MOTION

Actuator motion	Description	Advantages	Disadvantages	Examples
<b>Volume expansion</b>	The volume of the actuator changes, pushing the ink in all directions.	<ul style="list-style-type: none"> <li>◆ Simple construction in the case of thermal ink jet</li> <li>◆</li> </ul>	<ul style="list-style-type: none"> <li>◆ High energy is typically required to achieve volume expansion. This leads to thermal stress, cavitation, and kogation in thermal ink jet implementations</li> </ul>	<ul style="list-style-type: none"> <li>◆ Hewlett-Packard Thermal Inkjet</li> <li>◆ Canon Bubblejet</li> </ul>
<b>Linear, normal to chip surface</b>	The actuator moves in a direction normal to the print head surface. The nozzle is typically in the line of movement.	<ul style="list-style-type: none"> <li>◆ Efficient coupling to ink drops ejected normal to the surface</li> </ul>	<ul style="list-style-type: none"> <li>◆ High fabrication complexity may be required to achieve perpendicular motion</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ01, IJ02, IJ04, IJ07</li> <li>◆ IJ11, IJ14</li> </ul>
<b>Linear, parallel to chip surface</b>	The actuator moves parallel to the print head surface. Drop ejection may still be normal to the surface.	<ul style="list-style-type: none"> <li>◆ Suitable for planar fabrication</li> </ul>	<ul style="list-style-type: none"> <li>◆ Fabrication complexity</li> <li>◆ Friction</li> <li>◆ Stiction</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ12, IJ13, IJ15, IJ33,</li> <li>◆ IJ34, IJ35, IJ36</li> </ul>
<b>Membrane push</b>	An actuator with a high force but small area is used to push a stiff membrane that is in contact with the ink.	<ul style="list-style-type: none"> <li>◆ The effective area of the actuator becomes the membrane area</li> </ul>	<ul style="list-style-type: none"> <li>◆ Fabrication complexity</li> <li>◆ Actuator size</li> <li>◆ Difficulty of integration in a VLSI process</li> </ul>	<ul style="list-style-type: none"> <li>◆ 1982 Howkins USP 4,459,601</li> </ul>
<b>Rotary</b>	The actuator causes the rotation of some element, such a grill or impeller	<ul style="list-style-type: none"> <li>◆ Rotary levers may be used to increase travel</li> <li>◆ Small chip area requirements</li> </ul>	<ul style="list-style-type: none"> <li>◆ Device complexity</li> <li>◆ May have friction at a pivot point</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ05, IJ08, IJ13, IJ28</li> </ul>
<b>Bend</b>	The actuator bends when energized. This may be due to differential thermal expansion, piezoelectric expansion, magnetostriction, or other form of relative dimensional change.	<ul style="list-style-type: none"> <li>◆ A very small change in dimensions can be converted to a large motion.</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires the actuator to be made from at least two distinct layers, or to have a thermal difference across the actuator</li> </ul>	<ul style="list-style-type: none"> <li>◆ 1970 Kyser et al USP 3,946,398</li> <li>◆ 1973 Stemme USP 3,747,120</li> <li>◆ IJ03, IJ09, IJ10, IJ19</li> <li>◆ IJ23, IJ24, IJ25, IJ29</li> <li>◆ IJ30, IJ31, IJ33, IJ34</li> <li>◆ IJ35</li> </ul>
<b>Swivel</b>	The actuator swivels around a central pivot. This motion is suitable where there are opposite forces applied to opposite sides of the paddle, e.g. Lorenz force.	<ul style="list-style-type: none"> <li>◆ Allows operation where the net linear force on the paddle is zero</li> <li>◆ Small chip area requirements</li> </ul>	<ul style="list-style-type: none"> <li>◆ Inefficient coupling to the ink motion</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ06</li> </ul>
<b>Straighten</b>	The actuator is normally bent, and straightens when energized.	<ul style="list-style-type: none"> <li>◆ Can be used with shape memory alloys where the austenitic phase is planar</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires careful balance of stresses to ensure that the quiescent bend is accurate</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ26, IJ32</li> </ul>

<b>Double bend</b>	The actuator bends in one direction when one element is energized, and bends the other way when another element is energized.	<ul style="list-style-type: none"> <li>◆ One actuator can be used to power two nozzles.</li> <li>◆ Reduced chip size.</li> <li>◆ Not sensitive to ambient temperature</li> </ul>	<ul style="list-style-type: none"> <li>◆ Difficult to make the drops ejected by both bend directions identical.</li> <li>◆ A small efficiency loss compared to equivalent single bend actuators.</li> </ul>	◆ IJ36, IJ37, IJ38
<b>Shear</b>	Energizing the actuator causes a shear motion in the actuator material.	<ul style="list-style-type: none"> <li>◆ Can increase the effective travel of piezoelectric actuators</li> </ul>	<ul style="list-style-type: none"> <li>◆ Not readily applicable to other actuator mechanisms</li> </ul>	◆ 1985 Fishbeck USP 4,584,590
<b>Radial constriction</b>	The actuator squeezes an ink reservoir, forcing ink from a constricted nozzle.	<ul style="list-style-type: none"> <li>◆ Relatively easy to fabricate single nozzles from glass tubing as macroscopic structures</li> </ul>	<ul style="list-style-type: none"> <li>◆ High force required</li> <li>◆ Inefficient</li> <li>◆ Difficult to integrate with VLSI processes</li> </ul>	◆ 1970 Zoltan USP 3,683,212
<b>Coil / uncoil</b>	A coiled actuator uncoils or coils more tightly. The motion of the free end of the actuator ejects the ink.	<ul style="list-style-type: none"> <li>◆ Easy to fabricate as a planar VLSI process</li> <li>◆ Small area required, therefore low cost</li> </ul>	<ul style="list-style-type: none"> <li>◆ Difficult to fabricate for non-planar devices</li> <li>◆ Poor out-of-plane stiffness</li> </ul>	◆ IJ17, IJ21, IJ34, IJ35
<b>Bow</b>	The actuator bows (or buckles) in the middle when energized.	<ul style="list-style-type: none"> <li>◆ Can increase the speed of travel</li> <li>◆ Mechanically rigid</li> </ul>	<ul style="list-style-type: none"> <li>◆ Maximum travel is constrained</li> <li>◆ High force required</li> </ul>	◆ IJ16, IJ18, IJ27
<b>Push-Pull</b>	Two actuators control a shutter. One actuator pulls the shutter, and the other pushes it.	<ul style="list-style-type: none"> <li>◆ The structure is pinned at both ends, so has a high out-of-plane rigidity</li> </ul>	<ul style="list-style-type: none"> <li>◆ Not readily suitable for inkjets which directly push the ink</li> </ul>	◆ IJ18
<b>Curl inwards</b>	A set of actuators curl inwards to reduce the volume of ink that they enclose.	<ul style="list-style-type: none"> <li>◆ Good fluid flow to the region behind the actuator increases efficiency</li> </ul>	<ul style="list-style-type: none"> <li>◆ Design complexity</li> </ul>	◆ IJ20, IJ42
<b>Curl outwards</b>	A set of actuators curl outwards, pressurizing ink in a chamber surrounding the actuators, and expelling ink from a nozzle in the chamber.	<ul style="list-style-type: none"> <li>◆ Relatively simple construction</li> </ul>	<ul style="list-style-type: none"> <li>◆ Relatively large chip area</li> </ul>	◆ IJ43
<b>Iris</b>	Multiple vanes enclose a volume of ink. These simultaneously rotate, reducing the volume between the vanes.	<ul style="list-style-type: none"> <li>◆ High efficiency</li> <li>◆ Small chip area</li> </ul>	<ul style="list-style-type: none"> <li>◆ High fabrication complexity</li> <li>◆ Not suitable for pigmented inks</li> </ul>	◆ IJ22
<b>Acoustic vibration</b>	The actuator vibrates at a high frequency.	<ul style="list-style-type: none"> <li>◆ The actuator can be physically distant from the ink</li> <li>◆</li> </ul>	<ul style="list-style-type: none"> <li>◆ Large area required for efficient operation at useful frequencies</li> <li>◆ Acoustic coupling and crosstalk</li> <li>◆ Complex drive circuitry</li> <li>◆ Poor control of drop volume and position</li> </ul>	<ul style="list-style-type: none"> <li>◆ 1993 Hadimioglu et al, EUP 550,192</li> <li>◆ 1993 Elrod et al, EUP 572,220</li> </ul>

None	In various ink jet designs the actuator does not move.	♦ No moving parts ♦	♦ Various other tradeoffs are required to eliminate moving parts ♦	♦ Silverbrook, EP 0771 658 A2 and related patent applications ♦ Tone-jet
------	--	------------------------	---	---

# NOZZLE REFILL METHOD

Nozzle refill method	Description	Advantages	Disadvantages	Examples
<b>Surface tension</b>	After the actuator is energized, it typically returns rapidly to its normal position. This rapid return sucks in air through the nozzle opening. The ink surface tension at the nozzle then exerts a small force restoring the meniscus to a minimum area.	<ul style="list-style-type: none"> <li>◆ Fabrication simplicity</li> <li>◆ Operational simplicity</li> </ul>	<ul style="list-style-type: none"> <li>◆ Low speed</li> <li>◆ Surface tension force relatively small compared to actuator force</li> <li>◆ Long refill time usually dominates the total repetition rate</li> </ul>	<ul style="list-style-type: none"> <li>◆ Thermal inkjet</li> <li>◆ Piezoelectric inkjet</li> <li>◆ IJ01-IJ07, IJ10-IJ14</li> <li>◆ IJ16, IJ20, IJ22-IJ45</li> </ul>
<b>Shuttered oscillating ink pressure</b>	Ink to the nozzle chamber is provided at a pressure that oscillates at twice the drop ejection frequency. When a drop is to be ejected, the shutter is opened for 3 half cycles: drop ejection, actuator return, and refill.	<ul style="list-style-type: none"> <li>◆ High speed</li> <li>◆ Low actuator energy, as the actuator need only open or close the shutter, instead of ejecting the ink drop</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires common ink pressure oscillator</li> <li>◆ May not be suitable for pigmented inks</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ08, IJ13, IJ15, IJ17</li> <li>◆ IJ18, IJ19, IJ21</li> </ul>
<b>Refill actuator</b>	After the main actuator has ejected a drop a second (refill) actuator is energized. The refill actuator pushes ink into the nozzle chamber. The refill actuator returns slowly, to prevent its return from emptying the chamber again.	<ul style="list-style-type: none"> <li>◆ High speed, as the nozzle is actively refilled</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires two independent actuators per nozzle</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ09</li> </ul>
<b>Positive ink pressure</b>	The ink is held a slight positive pressure. After the ink drop is ejected, the nozzle chamber fills quickly as surface tension and ink pressure both operate to refill the nozzle.	<ul style="list-style-type: none"> <li>◆ High refill rate, therefore a high drop repetition rate is possible</li> </ul>	<ul style="list-style-type: none"> <li>◆ Surface spill must be prevented</li> <li>◆ Highly hydrophobic print head surfaces are required</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> <li>◆ Alternative for:</li> <li>◆ IJ01-IJ07, IJ10-IJ14</li> <li>◆ IJ16, IJ20, IJ22-IJ45</li> </ul>



**METHOD OF RESTRICTING BACK-FLOW THROUGH INLET**

<b>Inlet back-flow restriction method</b>	<b>Description</b>	<b>Advantages</b>	<b>Disadvantages</b>	<b>Examples</b>
<b>Long inlet channel</b>	The ink inlet channel to the nozzle chamber is made long and relatively narrow, relying on viscous drag to reduce inlet back-flow.	<ul style="list-style-type: none"> <li>◆ Design simplicity</li> <li>◆ Operational simplicity</li> <li>◆ Reduces crosstalk</li> </ul>	<ul style="list-style-type: none"> <li>◆ Restricts refill rate</li> <li>◆ May result in a relatively large chip area</li> <li>◆ Only partially effective</li> </ul>	<ul style="list-style-type: none"> <li>◆ Thermal inkjet</li> <li>◆ Piezoelectric inkjet</li> <li>◆ IJ42, IJ43</li> </ul>
<b>Positive ink pressure</b>	<p>The ink is under a positive pressure, so that in the quiescent state some of the ink drop already protrudes from the nozzle.</p> <p>This reduces the pressure in the nozzle chamber which is required to eject a certain volume of ink. The reduction in chamber pressure results in a reduction in ink pushed out through the inlet.</p>	<ul style="list-style-type: none"> <li>◆ Drop selection and separation forces can be reduced</li> <li>◆ Fast refill time</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires a method (such as a nozzle rim or effective hydrophobizing, or both) to prevent flooding of the ejection surface of the print head.</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> <li>◆ Possible operation of the following: <ul style="list-style-type: none"> <li>◆ IJ01-IJ07, IJ09-IJ12</li> <li>◆ IJ14, IJ16, IJ20, IJ22,</li> <li>◆ IJ23-IJ34, IJ36-IJ41</li> <li>◆ IJ44</li> </ul> </li> </ul>
<b>Baffle</b>	One or more baffles are placed in the inlet ink flow. When the actuator is energized, the rapid ink movement creates eddies which restrict the flow through the inlet. The slower refill process is unrestricted, and does not result in eddies.	<ul style="list-style-type: none"> <li>◆ The refill rate is not as restricted as the long inlet method.</li> <li>◆ Reduces crosstalk</li> </ul>	<ul style="list-style-type: none"> <li>◆ Design complexity</li> <li>◆ May increase fabrication complexity (e.g. Tektronix hot melt Piezoelectric print heads).</li> </ul>	<ul style="list-style-type: none"> <li>◆ HP Thermal Ink Jet</li> <li>◆ Tektronix piezoelectric ink jet</li> </ul>
<b>Flexible flap restricts inlet</b>	In this method recently disclosed by Canon, the expanding actuator (bubble) pushes on a flexible flap that restricts the inlet.	<ul style="list-style-type: none"> <li>◆ Significantly reduces back-flow for edge-shooter thermal ink jet devices</li> </ul>	<ul style="list-style-type: none"> <li>◆ Not applicable to most inkjet configurations</li> <li>◆ Increased fabrication complexity</li> <li>◆ Inelastic deformation of polymer flap results in creep over extended use</li> </ul>	<ul style="list-style-type: none"> <li>◆ Canon</li> </ul>

<b>Inlet filter</b>	A filter is located between the ink inlet and the nozzle chamber. The filter has a multitude of small holes or slots, restricting ink flow. The filter also removes particles which may block the nozzle.	<ul style="list-style-type: none"> <li>◆ Additional advantage of ink filtration</li> <li>◆ Ink filter may be fabricated with no additional process steps</li> </ul>	<ul style="list-style-type: none"> <li>◆ Restricts refill rate</li> <li>◆ May result in complex construction</li> <li>◆</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ04, IJ12, IJ24, IJ27</li> <li>◆ IJ29, IJ30</li> <li>◆</li> </ul>
<b>Small inlet compared to nozzle</b>	The ink inlet channel to the nozzle chamber has a substantially smaller cross section than that of the nozzle, resulting in easier ink egress out of the nozzle than out of the inlet.	<ul style="list-style-type: none"> <li>◆ Design simplicity</li> <li>◆</li> </ul>	<ul style="list-style-type: none"> <li>◆ Restricts refill rate</li> <li>◆ May result in a relatively large chip area</li> <li>◆ Only partially effective</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ02, IJ37, IJ44</li> <li>◆</li> </ul>
<b>Inlet shutter</b>	A secondary actuator controls the position of a shutter, closing off the ink inlet when the main actuator is energized.	<ul style="list-style-type: none"> <li>◆ Increases speed of the ink-jet print head operation</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires separate refill actuator and drive circuit</li> <li>◆</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ09</li> </ul>
<b>The inlet is located behind the ink-pushing surface</b>	The method avoids the problem of inlet back-flow by arranging the ink-pushing surface of the actuator between the inlet and the nozzle.	<ul style="list-style-type: none"> <li>◆ Back-flow problem is eliminated</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires careful design to minimize the negative pressure behind the paddle</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ01, IJ03, IJ05, IJ06</li> <li>◆ IJ07, IJ10, IJ11, IJ14</li> <li>◆ IJ16, IJ22, IJ23, IJ25</li> <li>◆ IJ28, IJ31, IJ32, IJ33</li> <li>◆ IJ34, IJ35, IJ36, IJ39</li> <li>◆ IJ40, IJ41</li> </ul>
<b>Part of the actuator moves to shut off the inlet</b>	The actuator and a wall of the ink chamber are arranged so that the motion of the actuator closes off the inlet.	<ul style="list-style-type: none"> <li>◆ Significant reductions in back-flow can be achieved</li> <li>◆ Compact designs possible</li> </ul>	<ul style="list-style-type: none"> <li>◆ Small increase in fabrication complexity</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ07, IJ20, IJ26, IJ38</li> </ul>
<b>Nozzle actuator does not result in ink back-flow</b>	In some configurations of ink jet, there is no expansion or movement of an actuator which may cause ink back-flow through the inlet.	<ul style="list-style-type: none"> <li>◆ Ink back-flow problem is eliminated</li> </ul>	<ul style="list-style-type: none"> <li>◆ None related to ink back-flow on actuation</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> <li>◆ Valve-jet</li> <li>◆ Tone-jet</li> <li>◆ IJ08, IJ13, IJ15, IJ17</li> <li>◆ IJ18, IJ19, IJ21</li> </ul>

# NOZZLE CLEARING METHOD

Nozzle Clearing method	Description	Advantages	Disadvantages	Examples
<b>Normal nozzle firing</b>	All of the nozzles are fired periodically, before the ink has a chance to dry. When not in use the nozzles are sealed (capped) against air.  The nozzle firing is usually performed during a special clearing cycle, after first moving the print head to a cleaning station.	◆ No added complexity on the print head	◆ May not be sufficient to displace dried ink	◆ Most ink jet systems ◆ IJ01- IJ07, IJ09-IJ12 ◆ IJ14, IJ16, IJ20, IJ22 ◆ IJ23- IJ34, IJ36-IJ45
<b>Extra power to ink heater</b>	In systems which heat the ink, but do not boil it under normal situations, nozzle clearing can be achieved by over-powering the heater and boiling ink at the nozzle.	◆ Can be highly effective if the heater is adjacent to the nozzle	◆ Requires higher drive voltage for clearing ◆ May require larger drive transistors	◆ Silverbrook, EP 0771 658 A2 and related patent applications
<b>Rapid succession of actuator pulses</b>	The actuator is fired in rapid succession. In some configurations, this may cause heat build-up at the nozzle which boils the ink, clearing the nozzle. In other situations, it may cause sufficient vibrations to dislodge clogged nozzles.	◆ Does not require extra drive circuits on the print head ◆ Can be readily controlled and initiated by digital logic	◆ Effectiveness depends substantially upon the configuration of the inkjet nozzle	◆ May be used with: ◆ IJ01-IJ07, IJ09- IJ11 ◆ IJ14, IJ16, IJ20, IJ22 ◆ IJ23-IJ25, IJ27-IJ34 ◆ IJ36-IJ45
<b>Extra power to ink pushing actuator</b>	Where an actuator is not normally driven to the limit of its motion, nozzle clearing may be assisted by providing an enhanced drive signal to the actuator.	◆ A simple solution where applicable	◆ Not suitable where there is a hard limit to actuator movement	◆ May be used with: ◆ IJ03, IJ09, IJ16, IJ20 ◆ IJ23, IJ24, IJ25, IJ27 ◆ IJ29, IJ30, IJ31, IJ32 ◆ IJ39, IJ40, IJ41, IJ42 ◆ IJ43, IJ44, IJ45
<b>Acoustic resonance</b>	An ultrasonic wave is applied to the ink chamber. This wave is of an appropriate amplitude and frequency to cause sufficient force at the nozzle to clear blockages. This is easiest to achieve if the ultrasonic wave is at a resonant frequency of the ink cavity.	◆ A high nozzle clearing capability can be achieved ◆ May be implemented at very low cost in systems which already include acoustic actuators	◆ High implementation cost if system does not already include an acoustic actuator	◆ IJ08, IJ13, IJ15, IJ17 ◆ IJ18, IJ19, IJ21

<b>Nozzle clearing plate</b>	A microfabricated plate is pushed against the nozzles. The plate has a post for every nozzle. The array of posts	<ul style="list-style-type: none"> <li>◆ Can clear severely clogged nozzles</li> </ul>	<ul style="list-style-type: none"> <li>◆ Accurate mechanical alignment is required</li> <li>◆ Moving parts are required</li> <li>◆ There is risk of damage to the nozzles</li> <li>◆ Accurate fabrication is required</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> </ul>
<b>Ink pressure pulse</b>	The pressure of the ink is temporarily increased so that ink streams from all of the nozzles. This may be used in conjunction with actuator energizing.	<ul style="list-style-type: none"> <li>◆ May be effective where other methods cannot be used</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires pressure pump or other pressure actuator</li> <li>◆ Expensive</li> <li>◆ Wasteful of ink</li> </ul>	<ul style="list-style-type: none"> <li>◆ May be used with all IJ series ink jets</li> </ul>
<b>Print head wiper</b>	A flexible 'blade' is wiped across the print head surface. The blade is usually fabricated from a flexible polymer, e.g. rubber or synthetic elastomer.	<ul style="list-style-type: none"> <li>◆ Effective for planar print head surfaces</li> <li>◆ Low cost</li> </ul>	<ul style="list-style-type: none"> <li>◆ Difficult to use if print head surface is non-planar or very fragile</li> <li>◆ Requires mechanical parts</li> <li>◆ Blade can wear out in high volume print systems</li> </ul>	<ul style="list-style-type: none"> <li>◆ Many ink jet systems</li> </ul>
<b>Separate ink boiling heater</b>	A separate heater is provided at the nozzle although the normal drop ejection mechanism does not require it. The heaters do not require individual drive circuits, as many nozzles can be cleared simultaneously, and no imaging is required.	<ul style="list-style-type: none"> <li>◆ Can be effective where other nozzle clearing methods cannot be used</li> <li>◆ Can be implemented at no additional cost in some inkjet configurations</li> </ul>	<ul style="list-style-type: none"> <li>◆ Fabrication complexity</li> </ul>	<ul style="list-style-type: none"> <li>◆ Can be used with many IJ series ink jets</li> </ul>

# NOZZLE PLATE CONSTRUCTION

Nozzle plate construction	Description	Advantages	Disadvantages	Examples
<b>Electroformed nickel</b>	A nozzle plate is separately fabricated from electroformed nickel, and bonded to the print head chip.	<ul style="list-style-type: none"> <li>◆ Fabrication simplicity</li> </ul>	<ul style="list-style-type: none"> <li>◆ High temperatures and pressures are required to bond nozzle plate</li> <li>◆ Minimum thickness constraints</li> <li>◆ Differential thermal expansion</li> </ul>	<ul style="list-style-type: none"> <li>◆ Hewlett Packard Thermal Inkjet</li> </ul>
<b>Laser ablated or drilled polymer</b>	Individual nozzle holes are ablated by an intense UV laser in a nozzle plate, which is typically a polymer such as polyimide or polysulphone	<ul style="list-style-type: none"> <li>◆ No masks required</li> <li>◆ Can be quite fast</li> <li>◆ Some control over nozzle profile is possible</li> <li>◆ Equipment required is relatively low cost</li> </ul>	<ul style="list-style-type: none"> <li>◆ Each hole must be individually formed</li> <li>◆ Special equipment required</li> <li>◆ Slow where there are many thousands of nozzles per print head</li> <li>◆ May produce thin burrs at exit holes</li> </ul>	<ul style="list-style-type: none"> <li>◆ Canon Bubblejet</li> <li>◆ 1988 Sercel et al., SPIE, Vol. 998 Excimer Beam Applications, pp. 76-83</li> <li>◆ 1993 Watanabe et al., USP 5,208,604</li> </ul>
<b>Silicon micro-machined</b>	A separate nozzle plate is micromachined from single crystal silicon, and bonded to the print head wafer.	<ul style="list-style-type: none"> <li>◆ High accuracy is attainable</li> </ul>	<ul style="list-style-type: none"> <li>◆ Two part construction</li> <li>◆ High cost</li> <li>◆ Requires precision alignment</li> <li>◆ Nozzles may be clogged by adhesive</li> </ul>	<ul style="list-style-type: none"> <li>◆ K. Bean, IEEE Transactions on Electron Devices, Vol. ED-25, No. 10, 1978, pp 1185-1195</li> <li>◆ Xerox 1990 Hawkins et al., USP 4,899,181</li> </ul>
<b>Glass capillaries</b>	Fine glass capillaries are drawn from glass tubing. This method has been used for making individual nozzles, but is difficult to use for bulk manufacturing of print heads with thousands of nozzles.	<ul style="list-style-type: none"> <li>◆ No expensive equipment required</li> <li>◆ Simple to make single nozzles</li> </ul>	<ul style="list-style-type: none"> <li>◆ Very small nozzle sizes are difficult to form</li> <li>◆ Not suited for mass production</li> </ul>	<ul style="list-style-type: none"> <li>◆ 1970 Zoltan USP 3,683,212</li> </ul>

<b>Monolithic, surface micro-machined using VLSI lithographic processes</b>	The nozzle plate is deposited as a layer using standard VLSI deposition techniques. Nozzles are etched in the nozzle plate using VLSI lithography and etching.	<ul style="list-style-type: none"> <li>◆ High accuracy (<math>&lt;1 \mu\text{m}</math>)</li> <li>◆ Monolithic</li> <li>◆ Low cost</li> <li>◆ Existing processes can be used</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires sacrificial layer under the nozzle plate to form the nozzle chamber</li> <li>◆ Surface may be fragile to the touch</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> <li>◆ IJ01, IJ02, IJ04, IJ11</li> <li>◆ IJ12, IJ17, IJ18, IJ20</li> <li>◆ IJ22, IJ24, IJ27, IJ28</li> <li>◆ IJ29, IJ30, IJ31, IJ32</li> <li>◆ IJ33, IJ34, IJ36, IJ37</li> <li>◆ IJ38, IJ39, IJ40, IJ41</li> <li>◆ IJ42, IJ43, IJ44</li> </ul>
<b>Monolithic, etched through substrate</b>	The nozzle plate is a buried etch stop in the wafer. Nozzle chambers are etched in the front of the wafer, and the wafer is thinned from the back side. Nozzles are then etched in the etch stop layer.	<ul style="list-style-type: none"> <li>◆ High accuracy (<math>&lt;1 \mu\text{m}</math>)</li> <li>◆ Monolithic</li> <li>◆ Low cost</li> <li>◆ No differential expansion</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires long etch times</li> <li>◆ Requires a support wafer</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ03, IJ05, IJ06, IJ07</li> <li>◆ IJ08, IJ09, IJ10, IJ13</li> <li>◆ IJ14, IJ15, IJ16, IJ19</li> <li>◆ IJ21, IJ23, IJ25, IJ26</li> </ul>
<b>No nozzle plate</b>	Various methods have been tried to eliminate the nozzles entirely, to prevent nozzle clogging. These include thermal bubble mechanisms and acoustic lens mechanisms	<ul style="list-style-type: none"> <li>◆ No nozzles to become clogged</li> </ul>	<ul style="list-style-type: none"> <li>◆ Difficult to control drop position accurately</li> <li>◆ Crosstalk problems</li> </ul>	<ul style="list-style-type: none"> <li>◆ Ricoh 1995 Sekiya et al USP 5,412,413</li> <li>◆ 1993 Hadimioglu et al EUP 550,192</li> <li>◆ 1993 Elrod et al EUP 572,220</li> </ul>
<b>Trough</b>	Each drop ejector has a trough through which a paddle moves. There is no nozzle plate.	<ul style="list-style-type: none"> <li>◆ Reduced manufacturing complexity</li> <li>◆ Monolithic</li> </ul>	<ul style="list-style-type: none"> <li>◆ Drop firing direction is sensitive to wicking.</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ35</li> </ul>
<b>Nozzle slit instead of individual nozzles</b>	The elimination of nozzle holes and replacement by a slit encompassing many actuator positions reduces nozzle clogging, but increases crosstalk due to ink surface waves	<ul style="list-style-type: none"> <li>◆ No nozzles to become clogged</li> </ul>	<ul style="list-style-type: none"> <li>◆ Difficult to control drop position accurately</li> <li>◆ Crosstalk problems</li> </ul>	<ul style="list-style-type: none"> <li>◆ 1989 Saito et al USP 4,799,068</li> </ul>

# DROP EJECTION DIRECTION

Ejection direction	Description	Advantages	Disadvantages	Examples
<b>Edge</b> (‘edge shooter’)	Ink flow is along the surface of the chip, and ink drops are ejected from the chip edge.	<ul style="list-style-type: none"> <li>◆ Simple construction</li> <li>◆ No silicon etching required</li> <li>◆ Good heat sinking via substrate</li> <li>◆ Mechanically strong</li> <li>◆ Ease of chip handling</li> </ul>	<ul style="list-style-type: none"> <li>◆ Nozzles limited to edge</li> <li>◆ High resolution is difficult</li> <li>◆ Fast color printing requires one print head per color</li> </ul>	<ul style="list-style-type: none"> <li>◆ Canon Bubblejet 1979 Endo et al GB patent 2,007,162</li> <li>◆ Xerox heater-in-pit 1990 Hawkins et al USP 4,899,181</li> <li>◆ Tone-jet</li> </ul>
<b>Surface</b> (‘roof shooter’)	Ink flow is along the surface of the chip, and ink drops are ejected from the chip surface, normal to the plane of the chip.	<ul style="list-style-type: none"> <li>◆ No bulk silicon etching required</li> <li>◆ Silicon can make an effective heat sink</li> <li>◆ Mechanical strength</li> </ul>	<ul style="list-style-type: none"> <li>◆ Maximum ink flow is severely restricted</li> </ul>	<ul style="list-style-type: none"> <li>◆ Hewlett-Packard TIJ 1982 Vaught et al USP 4,490,728</li> <li>◆ IJ02, IJ11, IJ12, IJ20</li> <li>◆ IJ22</li> </ul>
<b>Through chip, forward</b> (‘up shooter’)	Ink flow is through the chip, and ink drops are ejected from the front surface of the chip.	<ul style="list-style-type: none"> <li>◆ High ink flow</li> <li>◆ Suitable for pagewidth print</li> <li>◆ High nozzle packing density therefore low manufacturing cost</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires bulk silicon etching</li> </ul>	<ul style="list-style-type: none"> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> <li>◆ IJ04, IJ17, IJ18, IJ24</li> <li>◆ IJ27-IJ45</li> </ul>
<b>Through chip, reverse</b> (‘down shooter’)	Ink flow is through the chip, and ink drops are ejected from the rear surface of the chip.	<ul style="list-style-type: none"> <li>◆ High ink flow</li> <li>◆ Suitable for pagewidth print</li> <li>◆ High nozzle packing density therefore low manufacturing cost</li> </ul>	<ul style="list-style-type: none"> <li>◆ Requires wafer thinning</li> <li>◆ Requires special handling during manufacture</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ01, IJ03, IJ05, IJ06</li> <li>◆ IJ07, IJ08, IJ09, IJ10</li> <li>◆ IJ13, IJ14, IJ15, IJ16</li> <li>◆ IJ19, IJ21, IJ23, IJ25</li> <li>◆ IJ26</li> </ul>
<b>Through actuator</b>	Ink flow is through the actuator, which is not fabricated as part of the same substrate as the drive transistors.	<ul style="list-style-type: none"> <li>◆ Suitable for piezoelectric print heads</li> </ul>	<ul style="list-style-type: none"> <li>◆ Pagewidth print heads require several thousand connections to drive circuits</li> <li>◆ Cannot be manufactured in standard CMOS fabs</li> <li>◆ Complex assembly required</li> </ul>	<ul style="list-style-type: none"> <li>◆ Epson Stylus</li> <li>◆ Tektronix hot melt piezoelectric ink jets</li> </ul>

INK TYPE				
Ink type	Description	Advantages	Disadvantages	Examples
<b>Aqueous, dye</b>	Water based ink which typically contains: water, dye, surfactant, humectant, and biocide.  Modern ink dyes have high water-fastness, light fastness	<ul style="list-style-type: none"> <li>◆ Environmentally friendly</li> <li>◆ No odor</li> </ul>	<ul style="list-style-type: none"> <li>◆ Slow drying</li> <li>◆ Corrosive</li> <li>◆ Bleeds on paper</li> <li>◆ May strikethrough</li> <li>◆ Cockles paper</li> </ul>	<ul style="list-style-type: none"> <li>◆ Most existing inkjets</li> <li>◆ All IJ series ink jets</li> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> </ul>
<b>Aqueous, pigment</b>	Water based ink which typically contains: water, pigment, surfactant, humectant, and biocide.  Pigments have an advantage in reduced bleed, wicking and strikethrough.	<ul style="list-style-type: none"> <li>◆ Environmentally friendly</li> <li>◆ No odor</li> <li>◆ Reduced bleed</li> <li>◆ Reduced wicking</li> <li>◆ Reduced strikethrough</li> </ul>	<ul style="list-style-type: none"> <li>◆ Slow drying</li> <li>◆ Corrosive</li> <li>◆ Pigment may clog nozzles</li> <li>◆ Pigment may clog actuator mechanisms</li> <li>◆ Cockles paper</li> </ul>	<ul style="list-style-type: none"> <li>◆ IJ02, IJ04, IJ21, IJ26</li> <li>◆ IJ27, IJ30</li> <li>◆ Silverbrook, EP 0771 658 A2 and related patent applications</li> <li>◆ Piezoelectric ink-jets</li> <li>◆ Thermal ink jets (with significant restrictions)</li> </ul>
<b>Methyl Ethyl Ketone (MEK)</b>	MEK is a highly volatile solvent used for industrial printing on difficult surfaces such as aluminum cans.	<ul style="list-style-type: none"> <li>◆ Very fast drying</li> <li>◆ Prints on various substrates such as metals and plastics</li> </ul>	<ul style="list-style-type: none"> <li>◆ Odorous</li> <li>◆ Flammable</li> </ul>	<ul style="list-style-type: none"> <li>◆ All IJ series ink jets</li> </ul>
<b>Alcohol (ethanol, 2-butanol, and others)</b>	Alcohol based inks can be used where the printer must operate at temperatures below the freezing point of water. An example of this is in-camera consumer photographic printing.	<ul style="list-style-type: none"> <li>◆ Fast drying</li> <li>◆ Operates at sub-freezing temperatures</li> <li>◆ Reduced paper cockle</li> <li>◆ Low cost</li> </ul>	<ul style="list-style-type: none"> <li>◆ Slight odor</li> <li>◆ Flammable</li> </ul>	<ul style="list-style-type: none"> <li>◆ All IJ series ink jets</li> </ul>
<b>Phase change (hot melt)</b>	The ink is solid at room temperature, and is melted in the print head before jetting. Hot melt inks are usually wax based, with a melting point around 80 °C. After jetting the ink freezes almost instantly upon contacting the print medium or a transfer roller.	<ul style="list-style-type: none"> <li>◆ No drying time- ink instantly freezes on the print medium</li> <li>◆ Almost any print medium can be used</li> <li>◆ No paper cockle occurs</li> <li>◆ No wicking occurs</li> <li>◆ No bleed occurs</li> <li>◆ No strikethrough occurs</li> </ul>	<ul style="list-style-type: none"> <li>◆ High viscosity</li> <li>◆ Printed ink typically has a 'waxy' feel</li> <li>◆ Printed pages may 'block'</li> <li>◆ Ink temperature may be above the curie point of permanent magnets</li> <li>◆ Ink heaters consume power</li> <li>◆ Long warm-up time</li> </ul>	<ul style="list-style-type: none"> <li>◆ Tektronix hot melt piezoelectric ink jets</li> <li>◆ 1989 Nowak USP 4,820,346</li> <li>◆ All IJ series ink jets</li> </ul>
<b>Oil</b>	Oil based inks are extensively used in offset printing. They have advantages in improved characteristics on paper (especially no wicking or cockle). Oil soluble dyes and pigments are required.	<ul style="list-style-type: none"> <li>◆ High solubility medium for some dyes</li> <li>◆ Does not cockle paper</li> <li>◆ Does not wick through paper</li> </ul>	<ul style="list-style-type: none"> <li>◆ High viscosity: this is a significant limitation for use in inkjets, which usually require a low viscosity. Some short chain and multi-branched oils have a sufficiently low viscosity.</li> <li>◆ Slow drying</li> </ul>	<ul style="list-style-type: none"> <li>◆ All IJ series ink jets</li> </ul>



<b>Microemulsion</b>	A microemulsion is a stable, self forming emulsion of oil, water, and surfactant. The characteristic drop size is less than 100 nm, and is determined by the preferred curvature of the surfactant.	<ul style="list-style-type: none"><li>◆ Stops ink bleed</li><li>◆ High dye solubility</li><li>◆ Water, oil, and amphiphilic soluble dyes can be used</li><li>◆ Can stabilize pigment suspensions</li></ul>	<ul style="list-style-type: none"><li>◆ Viscosity higher than water</li><li>◆ Cost is slightly higher than water based ink</li><li>◆ High surfactant concentration required (around 5%)</li></ul>	<ul style="list-style-type: none"><li>◆ All IJ series ink jets</li></ul>
----------------------	---	--	---	--

Ink Jet Printing

———— A large number of new forms of ink jet printers have been developed to facilitate alternative ink jet technologies for the image processing and data distribution system. Various combinations of ink jet devices can be included in printer devices incorporated as part of the present invention. Australian Provisional Patent Applications relating to these ink jets which are specifically incorporated by cross reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

Australian Provisional Number	Filing Date	Title	US Patent/Patent Application and Filing Date
PO8066	15-Jul-97	Image Creation Method and Apparatus (IJ01)	<u>6,227,652</u> (July 10, 1998)
PO8072	15-Jul-97	Image Creation Method and Apparatus (IJ02)	<u>6,213,588</u> (July 10, 1998)
PO8040	15-Jul-97	Image Creation Method and Apparatus (IJ03)	<u>6,213,589</u> (July 10, 1998)
PO8071	15-Jul-97	Image Creation Method and Apparatus (IJ04)	<u>6,231,163</u> (July 10, 1998)
PO8047	15-Jul-97	Image Creation Method and Apparatus (IJ05)	<u>6,247,795</u> (July 10, 1998)
PO8035	15-Jul-97	Image Creation Method and Apparatus (IJ06)	<u>6,394,581</u> (July 10, 1998)
PO8044	15-Jul-97	Image Creation Method and Apparatus (IJ07)	<u>6,244,691</u> (July 10, 1998)
PO8063	15-Jul-97	Image Creation Method and Apparatus (IJ08)	<u>6,257,704</u> (July 10, 1998)
PO8057	15-Jul-97	Image Creation Method and Apparatus (IJ09)	<u>6,416,168</u> (July 10, 1998)
PO8056	15-Jul-97	Image Creation Method and Apparatus (IJ10)	<u>6,220,694</u> (July 10, 1998)
PO8069	15-Jul-97	Image Creation Method and Apparatus (IJ11)	<u>6,257,705</u> (July 10, 1998)
PO8049	15-Jul-97	Image Creation Method and Apparatus (IJ12)	<u>6,247,794</u> (July 10, 1998)
PO8036	15-Jul-97	Image Creation Method and Apparatus (IJ13)	<u>6,234,610</u> (July 10, 1998)

PO8048	15-Jul-97	Image Creation Method and Apparatus (IJ14)	<u>6,247,793</u> (July 10, 1998)
PO8070	15-Jul-97	Image Creation Method and Apparatus (IJ15)	<u>6,264,306</u> (July 10, 1998)
PO8067	15-Jul-97	Image Creation Method and Apparatus (IJ16)	<u>6,241,342</u> (July 10, 1998)
PO8001	15-Jul-97	Image Creation Method and Apparatus (IJ17)	<u>6,247,792</u> (July 10, 1998)
PO8038	15-Jul-97	Image Creation Method and Apparatus (IJ18)	<u>6,264,307</u> (July 10, 1998)
PO8033	15-Jul-97	Image Creation Method and Apparatus (IJ19)	<u>6,254,220</u> (July 10, 1998)
PO8002	15-Jul-97	Image Creation Method and Apparatus (IJ20)	<u>6,234,611</u> (July 10, 1998)
PO8068	15-Jul-97	Image Creation Method and Apparatus (IJ21)	<u>6,302,528</u> (July 10, 1998)
PO8062	15-Jul-97	Image Creation Method and Apparatus (IJ22)	<u>6,283,582</u> (July 10, 1998)
PO8034	15-Jul-97	Image Creation Method and Apparatus (IJ23)	<u>6,239,821</u> (July 10, 1998)
PO8039	15-Jul-97	Image Creation Method and Apparatus (IJ24)	<u>6,338,547</u> (July 10, 1998)
PO8041	15-Jul-97	Image Creation Method and Apparatus (IJ25)	<u>6,247,796</u> (July 10, 1998)
PO8004	15-Jul-97	Image Creation Method and Apparatus (IJ26)	<u>09/113,122</u> (July 10, 1998)
PO8037	15-Jul-97	Image Creation Method and Apparatus (IJ27)	<u>6,390,603</u> (July 10, 1998)
PO8043	15-Jul-97	Image Creation Method and Apparatus (IJ28)	<u>6,362,843</u> (July 10, 1998)
PO8042	15-Jul-97	Image Creation Method and Apparatus (IJ29)	<u>6,293,653</u> (July 10, 1998)
PO8064	15-Jul-97	Image Creation Method and Apparatus (IJ30)	<u>6,312,107</u> (July 10, 1998)
PO9389	23-Sep-97	Image Creation Method and Apparatus (IJ31)	<u>6,227,653</u> (July 10, 1998)
PO9391	23-Sep-97	Image Creation Method and Apparatus (IJ32)	<u>6,234,609</u> (July 10, 1998)

PP0888	12-Dec-97	Image Creation Method and Apparatus (IJ33)	<u>6,238,040</u> (July 10, 1998)
PP0891	12-Dec-97	Image Creation Method and Apparatus (IJ34)	<u>6,188,415</u> (July 10, 1998)
PP0890	12-Dec-97	Image Creation Method and Apparatus (IJ35)	<u>6,227,654</u> (July 10, 1998)
PP0873	12-Dec-97	Image Creation Method and Apparatus (IJ36)	<u>6,209,989</u> (July 10, 1998)
PP0993	12-Dec-97	Image Creation Method and Apparatus (IJ37)	<u>6,247,791</u> (July 10, 1998)
PP0890	12-Dec-97	Image Creation Method and Apparatus (IJ38)	<u>6,336,710</u> (July 10, 1998)
PP1398	19-Jan-98	An Image Creation Method and Apparatus (IJ39)	<u>6,217,153</u> (July 10, 1998)
PP2592	25-Mar-98	An Image Creation Method and Apparatus (IJ40)	<u>6,416,167</u> (July 10, 1998)
PP2593	25-Mar-98	Image Creation Method and Apparatus (IJ41)	<u>6,243,113</u> (July 10, 1998)
PP3991	9-Jun-98	Image Creation Method and Apparatus (IJ42)	<u>6,283,581</u> (July 10, 1998)
PP3987	9-Jun-98	Image Creation Method and Apparatus (IJ43)	<u>6,247,790</u> (July 10, 1998)
PP3985	9-Jun-98	Image Creation Method and Apparatus (IJ44)	<u>6,260,953</u> (July 10, 1998)
PP3983	9-Jun-98	Image Creation Method and Apparatus (IJ45)	<u>6,267,469</u> (July 10, 1998)

#### Ink Jet Manufacturing

Further, the present application may utilize advanced semiconductor fabrication techniques in the construction of large arrays of ink jet printers. Suitable manufacturing techniques are described in the following Australian provisional patent specifications incorporated here by cross-reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

Australian Provisional Number	Filing Date	Title	US Patent/Patent Application and Filing Date
PO7935	15-Jul-97	A Method of Manufacture of an Image	<u>6,224,780</u>

		Creation Apparatus (IJM01)	<u>(July 10, 1998)</u>
PO7936	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM02)	<u>6,235,212</u> <u>(July 10, 1998)</u>
PO7937	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM03)	<u>6,280,643</u> <u>(July 10, 1998)</u>
PO8061	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM04)	<u>6,284,147</u> <u>(July 10, 1998)</u>
PO8054	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM05)	<u>6,214,244</u> <u>(July 10, 1998)</u>
PO8065	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM06)	<u>6,071,750</u> <u>(July 10, 1998)</u>
PO8055	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM07)	<u>6,267,905</u> <u>(July 10, 1998)</u>
PO8053	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM08)	<u>6,251,298</u> <u>(July 10, 1998)</u>
PO8078	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM09)	<u>6,258,285</u> <u>(July 10, 1998)</u>
PO7933	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM10)	<u>6,225,138</u> <u>(July 10, 1998)</u>
PO7950	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM11)	<u>6,241,904</u> <u>(July 10, 1998)</u>
PO7949	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM12)	<u>6,299,786</u> <u>(July 10, 1998)</u>
PO8060	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM13)	<u>09/113,124</u> <u>(July 10, 1998)</u>
PO8059	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM14)	<u>6,231,773</u> <u>(July 10, 1998)</u>
PO8073	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM15)	<u>6,190,931</u> <u>(July 10, 1998)</u>
PO8076	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM16)	<u>6,248,249</u> <u>(July 10, 1998)</u>
PO8075	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM17)	<u>6,290,862</u> <u>(July 10, 1998)</u>
PO8079	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM18)	<u>6,241,906</u> <u>(July 10, 1998)</u>
PO8050	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM19)	<u>09/113,116</u> <u>(July 10, 1998)</u>
PO8052	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM20)	<u>6,241,905</u> <u>(July 10, 1998)</u>

PO7948	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM21)	<u>6,451,216</u> (July 10, 1998)
PO7951	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM22)	<u>6,231,772</u> (July 10, 1998)
PO8074	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM23)	<u>6,274,056</u> (July 10, 1998)
PO7941	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM24)	<u>6,290,861</u> (July 10, 1998)
PO8077	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM25)	<u>6,248,248</u> (July 10, 1998)
PO8058	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM26)	<u>6,306,671</u> (July 10, 1998)
PO8051	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM27)	<u>6,331,258</u> (July 10, 1998)
PO8045	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM28)	<u>6,110,754</u> (July 10, 1998)
PO7952	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM29)	<u>6,294,101</u> (July 10, 1998)
PO8046	15-Jul-97	A Method of Manufacture of an Image Creation Apparatus (IJM30)	<u>6,416,679</u> (July 10, 1998)
PO8503	11-Aug-97	A Method of Manufacture of an Image Creation Apparatus (IJM30a)	<u>6,264,849</u> (July 10, 1998)
PO9390	23-Sep-97	A Method of Manufacture of an Image Creation Apparatus (IJM31)	<u>6,254,793</u> (July 10, 1998)
PO9392	23-Sep-97	A Method of Manufacture of an Image Creation Apparatus (IJM32)	<u>6,235,211</u> (July 10, 1998)
PP0889	12-Dec-97	A Method of Manufacture of an Image Creation Apparatus (IJM35)	<u>6,235,211</u> (July 10, 1998)
PP0887	12-Dec-97	A Method of Manufacture of an Image Creation Apparatus (IJM36)	<u>6,264,850</u> (July 10, 1998)
PP0882	12-Dec-97	A Method of Manufacture of an Image Creation Apparatus (IJM37)	<u>6,258,284</u> (July 10, 1998)
PP0874	12-Dec-97	A Method of Manufacture of an Image Creation Apparatus (IJM38)	<u>6,258,284</u> (July 10, 1998)
PP1396	19-Jan-98	A Method of Manufacture of an Image Creation Apparatus (IJM39)	<u>6,228,668</u> (July 10, 1998)
PP2591	25-Mar-98	A Method of Manufacture of an Image	<u>6,180,427</u>

		Creation Apparatus (IJM41)	(July 10, 1998)
PP3989	9-Jun-98	A Method of Manufacture of an Image Creation Apparatus (IJM40)	<u>6,171,875</u> (July 10, 1998)
PP3990	9-Jun-98	A Method of Manufacture of an Image Creation Apparatus (IJM42)	<u>6,267,904</u> (July 10, 1998)
PP3986	9-Jun-98	A Method of Manufacture of an Image Creation Apparatus (IJM43)	<u>6,245,247</u> (July 10, 1998)
PP3984	9-Jun-98	A Method of Manufacture of an Image Creation Apparatus (IJM44)	<u>6,245,247</u> (July 10, 1998)
PP3982	9-Jun-98	A Method of Manufacture of an Image Creation Apparatus (IJM45)	<u>6,231,148</u> (July 10, 1998)

### Fluid Supply

Further, the present application may utilize an ink delivery system to the ink jet head. Delivery systems relating to the supply of ink to a series of ink jet nozzles are described in the following Australian provisional patent specifications, the disclosure of which are hereby incorporated by cross-reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

Australian Provisional Number	Filing Date	Title	US Patent/Patent Application and Filing Date
PO8003	15-Jul-97	Supply Method and Apparatus (F1)	<u>6,350,023</u> (July 10, 1998)
PO8005	15-Jul-97	Supply Method and Apparatus (F2)	<u>6,318,849</u> (July 10, 1998)
PO9404	23-Sep-97	A Device and Method (F3)	<u>09/113,101</u> (July 10, 1998)

### MEMS Technology

Further, the present application may utilize advanced semiconductor microelectromechanical techniques in the construction of large arrays of ink jet printers. Suitable microelectromechanical techniques are described in the following Australian provisional patent specifications incorporated here by cross-reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

Australian Provisional Number	Filing Date	Title	US Patent/Patent Application and Filing Date
PO7943	15-Jul-97	A device (MEMS01)	
PO8006	15-Jul-97	A device (MEMS02)	<u>6,087,638</u> <u>(July 10, 1998)</u>
PO8007	15-Jul-97	A device (MEMS03)	<u>09/113,093</u> <u>(July 10, 1998)</u>
PO8008	15-Jul-97	A device (MEMS04)	<u>6,340,222</u> <u>(July 10, 1998)</u>
PO8010	15-Jul-97	A device (MEMS05)	<u>6,041,600</u> <u>(July 10, 1998)</u>
PO8011	15-Jul-97	A device (MEMS06)	<u>6,299,300</u> <u>(July 10, 1998)</u>
PO7947	15-Jul-97	A device (MEMS07)	<u>6,067,797</u> <u>(July 10, 1998)</u>
PO7945	15-Jul-97	A device (MEMS08)	<u>09/113,081</u> <u>(July 10, 1998)</u>
PO7944	15-Jul-97	A device (MEMS09)	<u>6,286,935</u> <u>(July 10, 1998)</u>
PO7946	15-Jul-97	A device (MEMS10)	<u>6,044,646</u> <u>(July 10, 1998)</u>
PO9393	23-Sep-97	A Device and Method (MEMS11)	<u>09/113,065</u> <u>(July 10, 1998)</u>
PP0875	12-Dec-97	A Device (MEMS12)	<u>09/113,078</u> <u>(July 10, 1998)</u>
PP0894	12-Dec-97	A Device and Method (MEMS13)	<u>09/113,075</u> <u>(July 10, 1998)</u>

#### IR Technologies

5

Further, the present application may include the utilization of a disposable camera system such as those described in the following Australian provisional patent specifications incorporated here by cross-reference. The serial numbers of respective corresponding US patent applications are



also provided for the sake of convenience.

Australian Provisional Number	Filing Date	Title	US Patent/Patent Application and Filing Date
PP0895	12-Dec-97	An Image Creation Method and Apparatus (IR01)	6,231,148 (July 10, 1998)
PP0870	12-Dec-97	A Device and Method (IR02)	09/113,106 (July 10, 1998)
PP0869	12-Dec-97	A Device and Method (IR04)	6,293,658 (July 10, 1998)
PP0887	12-Dec-97	Image Creation Method and Apparatus (IR05)	09/113,104 (July 10, 1998)
PP0885	12-Dec-97	An Image Production System (IR06)	6,238,033 (July 10, 1998)
PP0884	12-Dec-97	Image Creation Method and Apparatus (IR10)	6,312,070 (July 10, 1998)
PP0886	12-Dec-97	Image Creation Method and Apparatus (IR12)	6,238,111 (July 10, 1998)
PP0871	12-Dec-97	A Device and Method (IR13)	09/113,086 (July 10, 1998)
PP0876	12-Dec-97	An Image Processing Method and Apparatus (IR14)	09/113,094 (July 10, 1998)
PP0877	12-Dec-97	A Device and Method (IR16)	6,378,970 (July 10, 1998)
PP0878	12-Dec-97	A Device and Method (IR17)	6,196,739 (July 10, 1998)
PP0879	12-Dec-97	A Device and Method (IR18)	09/112,774 (July 10, 1998)
PP0883	12-Dec-97	A Device and Method (IR19)	6,270,182 (July 10, 1998)
PP0880	12-Dec-97	A Device and Method (IR20)	6,152,619 (July 10, 1998)
PP0881	12-Dec-97	A Device and Method (IR21)	09/113,092 (July 10, 1998)

#### DotCard Technologies

5

— Further, the present application may include the utilization of a data distribution system such as that described in the following Australian provisional patent specifications incorporated

here by cross-reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

Australian Provisional Number	Filing Date	Title	US Patent/Patent Application and Filing Date
PP2370	16-Mar-98	Data Processing Method and Apparatus (Dot01)	09/112,781 (July 10, 1998)
PP2371	16-Mar-98	Data Processing Method and Apparatus (Dot02)	09/113,052 (July 10, 1998)

#### Arteam Technologies

5

Further, the present application may include the utilization of camera and data processing techniques such as an Arteam type device as described in the following Australian provisional patent specifications incorporated here by cross-reference. The serial numbers of respective corresponding US patent applications are also provided for the sake of convenience.

Australian Provisional Number	Filing Date	Title	US Patent/Patent Application and Filing Date
PO7991	15-Jul-97	Image Processing Method and Apparatus (ART01)	09/113,060 (July 10, 1998)
PO7988	15-Jul-97	Image Processing Method and Apparatus (ART02)	6,476,863 (July 10, 1998)
PO7993	15-Jul-97	Image Processing Method and Apparatus (ART03)	09/113,073 (July 10, 1998)
PO9395	23-Sep-97	Data Processing Method and Apparatus (ART04)	6,322,181 (July 10, 1998)
PO8017	15-Jul-97	Image Processing Method and Apparatus (ART06)	09/112,747 (July 10, 1998)
PO8014	15-Jul-97	Media Device (ART07)	6,227,648 (July 10, 1998)
PO8025	15-Jul-97	Image Processing Method and Apparatus (ART08)	09/112,750 (July 10, 1998)
PO8032	15-Jul-97	Image Processing Method and Apparatus (ART09)	09/112,746 (July 10, 1998)
PO7999	15-Jul-97	Image Processing Method and Apparatus (ART10)	09/112,743 (July 10, 1998)
PO7998	15-Jul-97	Image Processing Method and	09/112,742

		Apparatus (ART11)	<u>(July 10, 1998)</u>
PO8031	15-Jul-97	Image Processing Method and Apparatus (ART12)	<u>09/112,741</u> <u>(July 10, 1998)</u>
PO8030	15-Jul-97	Media Device (ART13)	<u>6,196,541</u> <u>(July 10, 1998)</u>
PO7997	15-Jul-97	Media Device (ART15)	<u>6,195,150</u> <u>(July 10, 1998)</u>
PO7979	15-Jul-97	Media Device (ART16)	<u>6,362,868</u> <u>(July 10, 1998)</u>
PO8015	15-Jul-97	Media Device (ART17)	<u>09/112,738</u> <u>(July 10, 1998)</u>
PO7978	15-Jul-97	Media Device (ART18)	<u>09/113,067</u> <u>(July 10, 1998)</u>
PO7982	15-Jul-97	Data Processing Method and Apparatus (ART19)	<u>6,431,669</u> <u>(July 10, 1998)</u>
PO7989	15-Jul-97	Data Processing Method and Apparatus (ART20)	<u>6,362,869</u> <u>(July 10, 1998)</u>
PO8019	15-Jul-97	Media Processing Method and Apparatus (ART21)	<u>6,472,052</u> <u>(July 10, 1998)</u>
PO7980	15-Jul-97	Image Processing Method and Apparatus (ART22)	<u>6,356,715</u> <u>(July 10, 1998)</u>
PO8018	15-Jul-97	Image Processing Method and Apparatus (ART24)	<u>09/112,777</u> <u>(July 10, 1998)</u>
PO7938	15-Jul-97	Image Processing Method and Apparatus (ART25)	<u>09/113,224</u> <u>(July 10, 1998)</u>
PO8016	15-Jul-97	Image Processing Method and Apparatus (ART26)	<u>6,366,693</u> <u>(July 10, 1998)</u>
PO8024	15-Jul-97	Image Processing Method and Apparatus (ART27)	<u>6,329,990</u> <u>(July 10, 1998)</u>
PO7940	15-Jul-97	Data Processing Method and Apparatus (ART28)	<u>09/113,072</u> <u>(July 10, 1998)</u>
PO7939	15-Jul-97	Data Processing Method and Apparatus (ART29)	<u>09/112,785</u> <u>(July 10, 1998)</u>
PO8501	11-Aug-97	Image Processing Method and Apparatus (ART30)	<u>6,137,500</u> <u>(July 10, 1998)</u>
PO8500	11-Aug-97	Image Processing Method and Apparatus (ART31)	<u>09/112,796</u> <u>(July 10, 1998)</u>
PO7987	15-Jul-97	Data Processing Method and Apparatus	<u>09/113,071</u>

		(ART32)	(July 10, 1998)
PO8022	15-Jul-97	Image Processing Method and Apparatus (ART33)	<u>6,398,328</u> (July 10, 1998)
PO8497	11-Aug-97	Image Processing Method and Apparatus (ART34)	<u>09/113,090</u> (July 10, 1998)
PO8020	15-Jul-97	Data Processing Method and Apparatus (ART38)	<u>6,431,704</u> (July 10, 1998)
PO8023	15-Jul-97	Data Processing Method and Apparatus (ART39)	<u>09/113,222</u> (July 10, 1998)
PO8504	11-Aug-97	Image Processing Method and Apparatus (ART42)	<u>09/112,786</u> (July 10, 1998)
PO8000	15-Jul-97	Data Processing Method and Apparatus (ART43)	<u>6,415,054</u> (July 10, 1998)
PO7977	15-Jul-97	Data Processing Method and Apparatus (ART44)	<u>09/112,782</u> (July 10, 1998)
PO7934	15-Jul-97	Data Processing Method and Apparatus (ART45)	<u>09/113,056</u> (July 10, 1998)
PO7990	15-Jul-97	Data Processing Method and Apparatus (ART46)	<u>09/113,059</u> (July 10, 1998)
PO8499	11-Aug-97	Image Processing Method and Apparatus (ART47)	<u>6,486,886</u> (July 10, 1998)
PO8502	11-Aug-97	Image Processing Method and Apparatus (ART48)	<u>6,381,361</u> (July 10, 1998)
PO7981	15-Jul-97	Data Processing Method and Apparatus (ART50)	<u>6,317,192</u> (July 10, 1998)
PO7986	15-Jul-97	Data Processing Method and Apparatus (ART51)	<u>09/113,057</u> (July 10, 1998)
PO7983	15-Jul-97	Data Processing Method and Apparatus (ART52)	<u>09/113,054</u> (July 10, 1998)
PO8026	15-Jul-97	Image Processing Method and Apparatus (ART53)	<u>09/112,752</u> (July 10, 1998)
PO8027	15-Jul-97	Image Processing Method and Apparatus (ART54)	<u>09/112,759</u> (July 10, 1998)
PO8028	15-Jul-97	Image Processing Method and Apparatus (ART56)	<u>09/112,757</u> (July 10, 1998)
PO9394	23-Sep-97	Image Processing Method and Apparatus (ART57)	<u>6,357,135</u>

			<u>(July 10, 1998)</u>
PO9396	23-Sep-97	Data Processing Method and Apparatus (ART58)	<u>09/113,107</u> <u>(July 10, 1998)</u>
PO9397	23-Sep-97	Data Processing Method and Apparatus (ART59)	<u>6,271,931</u> <u>(July 10, 1998)</u>
PO9398	23-Sep-97	Data Processing Method and Apparatus (ART60)	<u>6,353,772</u> <u>(July 10, 1998)</u>
PO9399	23-Sep-97	Data Processing Method and Apparatus (ART61)	<u>6,106,147</u> <u>(July 10, 1998)</u>
PO9400	23-Sep-97	Data Processing Method and Apparatus (ART62)	<u>09/112,790</u> <u>(July 10, 1998)</u>
PO9401	23-Sep-97	Data Processing Method and Apparatus (ART63)	<u>6,304,291</u> <u>(July 10, 1998)</u>
PO9402	23-Sep-97	Data Processing Method and Apparatus (ART64)	<u>09/112,788</u> <u>(July 10, 1998)</u>
PO9403	23-Sep-97	Data Processing Method and Apparatus (ART65)	<u>6,305,770</u> <u>(July 10, 1998)</u>
PO9405	23-Sep-97	Data Processing Method and Apparatus (ART66)	<u>6,289,262</u> <u>(July 10, 1998)</u>
PP0959	16-Dec-97	A Data Processing Method and Apparatus (ART68)	<u>6,315,200</u> <u>(July 10, 1998)</u>
PP1397	19-Jan-98	A Media Device (ART69)	<u>6,217,165</u> <u>(July 10, 1998)</u>